

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

क्रमांक: WEC DHOIPUR/2026-27/2331

दिनांक:- 01/07/2026

ई-निविदा सूचना संख्या.13/2026-27

Two Bid System

अभियांत्रिकी महाविद्यालय, धौलपुर में Civil Engineering Department Lab की आपूर्ति, स्थापना एवं कमिंशनिंग हेतु निर्माता/अधिकृत आपूर्तिकर्ताओं/विक्रेताओं से मोहरबंद खुली निविदाएं निर्धारित प्रपत्र में (तकनीकी एवं वित्तीय) दिनांक 28.7.26 को 5 PM बजे तक आमंत्रित की जाती है। प्राप्त निविदाओं की तकनीकी निविदाएं दिनांक 28.7.26 को प्रातः 6 PM बजे खोली जावेगी।

क्र.सं.	लैब सामग्री का विवरण	अनुमानित लागत	बोली प्रतिभूति राशि (रूपये में)	निविदा प्रपत्र शुल्क (रूपये में)
1.	Civil Engineering Department Lab की आपूर्ति, स्थापना एवं कमिंशनिंग	85.00 लाख	170000.00	500.00

निविदा से सम्बन्धित सम्पूर्ण विवरण, बोली प्रपत्र एवं विस्तृत शर्तें वेबसाइट <http://eproc.rajasthan.gov.in> and <http://sppp.rajasthan.gov.in> (राजस्थान राज्य लोक उपापन पोर्टल) एवं महाविद्यालय की वेबसाइट www.ecd.ac.in पर देखा जा सकता है।

UBN:

Blgst

प्राचार्य
अभियांत्रिकी महाविद्यालय
धौलपुर

प्रतिलिपि :- निम्न को सूचनार्थ एवं आवश्यक कार्यवाही हेतु प्रेषित है:-

1. श्रीमान निजी सचिव, कुलपति महोदय, राजस्थान तकनीकी विश्वविद्यालय, कोटा
2. श्रीमान कुलसचिव महोदय, राजस्थान तकनीकी विश्वविद्यालय, कोटा
3. संयुक्त शासन सचिव, तकनीकी शिक्षा विभाग, राजस्थान सरकार
4. आयुक्त, कॉलेज शिक्षा, राजस्थान, जयपुर।
5. कोषाधिकारी/वरिष्ठ लेखाधिकारी कलेक्ट्रेट धौलपुर।
6. संबंधित विभागाधिकारी
7. जिला सूचना एवं जनसम्पर्क अधिकारी, धौलपुर।
8. रक्षित पत्रावली।

Brajesh

Blgst

(Dr. Ramesh Surastaw)

Wishnu

Wishnu

Kishan
Treasury officer
Dholpur

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

क्रमांक:

दिनांक:-

विस्तृत ई-निविदा सूचना - ¹³ /2026-27

अभियांत्रिकी महाविद्यालय, धौलपुर में Civil Engineering Department Lab की आपूर्ति, स्थापना एवं कमिश्निंग हेतु निर्माता/अधिकृत आपूर्तिकर्ताओं/विक्रेताओं से मोहरबंद खुली निविदाएं निर्धारित प्रपत्र में (तकनीकी एवं वित्तीय) दिनांक 28/12/26 को 5 PM बजे तक आमंत्रित की जाती है। प्राप्त निविदाओं की तकनीकी निविदाएं दिनांक 28/12/26 को 6 PM बजे खोली जावेगी।

निविदा से सम्बन्धित सम्पूर्ण विवरण, बोली प्रपत्र एवं विस्तृत शर्तें विभागीय वेबसाईट <http://eproc.rajasthan.gov.in> and <http://sppp.rajasthan.gov.in> (राजस्थान राज्य लोक उपापन पोर्टल) एवं महाविद्यालय की वेबसाईट www.ecd.ac.in पर देखा जा सकता है।

क्र.सं.	सामान का विवरण	अनुमानित लागत	बोली प्रतिभूति राशि (रूपये में)	निविदा प्रपत्र शुल्क (रूपये में)
2.	Civil Engineering Department Lab की आपूर्ति, स्थापना एवं कमिश्निंग	85.00 लाख	170000.00	500.00

विशेष विवरण-

क्र.सं.	विवरण	दिनांक	समय
1	निविदा जारी करने की दिनांक एवं समय	दि 04/07/26	5 PM
2	निविदा प्रपत्र डाउनलोड प्रारंभ करने की दिनांक एवं समय	दि 04/07/26	8 PM
3	निविदा अपलोड करने की अंतिम दिनांक एवं समय	दि 28/07/26	5 PM
4	सामग्री के नमूने जमा करवाने की दिनांक एवं समय	दि 28/07/26	5 PM
5	तकनीकी बोली खोले जाने की दिनांक एवं समय	दि 28/7/26	6 PM

- बोली प्रपत्र शुल्क, प्रतिभूति राशि एवं RISL फीस DD के माध्यम से प्राचार्य अभियांत्रिकी महाविद्यालय धौलपुर में जमा कराना होगा। बोली प्रपत्र शुल्क, बोली प्रतिभूति/बोली प्रतिभूति घोषणा के बिना प्राप्त बोली पर कोई विचार नहीं किया जावेगा। बोली प्रतिभूति घोषणा के संबंध में वित्त (जी.एफ.एण्ड ए.आर.) विभाग द्वारा जारी परिपत्र दिनांक 23.12.2020 के प्रावधान लागू होंगे।
- प्राप्त निविदाओं को क्रय समिति द्वारा उपस्थित बोलीदाताओं के समक्ष उपरोक्तानुसार निर्धारित दिनांक व समय पर खोली जायेगी।
- बोली की वैधता निविदा जमा कराने की दिनांक से 90 दिवस तक मान्य होगी।
- निविदादाता निविदा भरने से पूर्व निविदा प्रपत्र का सावधानी पूर्वक गहन अध्ययन कर निविदा में वर्णित में अपेक्षित समस्त अर्हताओं एवं दस्तावेजों को स्वयं सत्यापन कर समाधान कर ले कि वह इस बोली हेतु समस्त पात्रताएं पूर्ण करता है। किसी भी स्तर पर गलत सूचनाएं, मिथ्या दस्तावेज आदि पाए जाने पर बोली अस्वीकार कर दी जाएगी।
- बोली में आमंत्रित दरें अनुमोदित किये जाने की दिनांक से एक वर्ष के लिये विधिमान्य होगी।

K. K. K.
Treasurer
Officer
shop

Atgts

M. K. K. *M. K. K.* *M. K. K.* *M. K. K.*

6. क्रय की जाने वाली सामग्री के कैंटलॉग गय स्पेशिफिकेशन के तकनीकी बोली के साथ प्रस्तुत किये जावे जिनका अवलोकन उपापन समिति/तकनीकी समिति द्वारा किया जायेगा।
7. क्रय की जाने वाली सामग्री की सप्लाई एफ.ओ.आर. कार्यालय प्राचार्य अभियांत्रिकी महाविद्यालय धौलपुर में करनी होगी।
8. कार्य आदेश जारी करने की दिनांक से 40 दिवस की अवधि के भीतर फर्म द्वारा आईटम सप्लाई, स्थापना एवं कमिशनिंग करना होगा। निर्धारित समयावधि में सामग्री सप्लाई नहीं करने पर नियमानुसार परिसमापित नुकसानी (L.D.) की कटौती की जावेगी।
9. बोली प्रतिभूति/कार्य सम्पादन प्रतिभूति राशि में छूट के लिये आयुक्त, उद्योग विभाग, राजस्थान जयपुर के पास रजिस्ट्रीकृत कुटीर एवं लघु उद्योग विभाग उन मदों के सम्बन्ध में जिसके लिये वे इस रूप में रजिस्ट्रीकृत हैं, सामान का क्रय राजस्थान के उद्योग के अधिमान नियम 1995 के नियम-8 के अनुसार अपेक्षित कार्यवाही जो वित्त (जीएफ एण्ड एआर) विभाग के आदेश क्रमांक : प1(1)वित्त/सा.नि.लेनि./2007 दिनांक 19.10.2010 परिपत्र संख्या 24/2010 में वर्णित है के अनुसार प्रस्तुत किया जाना अनिवार्य है। अन्यथा बोली बयाना/कार्य सम्पादन प्रतिभूति राशि में छूट देय नहीं होगा।
10. यदि उपापन संस्था परिस्थितियों में परिवर्तन के कारण उपापन की कोई विषयवस्तु उपाप्त नहीं करती है या बोली दस्तावेजों में विनिर्दिष्ट परिमाण से कम उपाप्त करती है तो बोली लगाने वाला बोली दस्तावेजों में अन्यथा उपबंधित के सिवाय, किसी भी दावे या प्रतिकर का हकदार नहीं होगा।
11. अतिरिक्त मदों या अतिरिक्त परिमाणों के लिए पुनरादेश, यदि यह बोली दस्तावेजों में उपबंधित हो, संविदा में दी गयी दरों और शर्तों पर दिये जा सकेंगे यदि मूल आदेश खुली बोली आमंत्रित करने के पश्चात् दिया गया था। प्रदाय या पूर्ण हाने की कालावधि भी आनुपातिक रूप से बढ़ायी जा सकती। पुनरादेश की सीमाएँ राजस्थान लोक उपापन में पारदर्शिता नियम, 2013 के नियम 73 के अनुसार होगी।
12. विशेष परिस्थितियों में राज. लोक उपापन में पारदर्शिता नियम 2013 के नियम 74 के अनुसार कार्य Fair, Transparent & equitable manner से विभाजित किया जा सकेगा।
13. इस निविदा पर सामान्य वित्तीय एवं लेखा नियम, राजस्थान लोक उपापन में पारदर्शिता अधिनियम 2012 एवं राजस्थान लोक उपापन में पारदर्शिता नियम 2013 के नियम व प्रावधान तथा इनमें समय समय पर किए गए संशोधन लागू/प्रभावी होंगे।
14. निविदा से सम्बन्धित सभी अधिकार विभागाध्यक्ष के पास सुरक्षित रहेंगे। किसी भी बोली को स्वीकार या अस्वीकार करने तथा बोली प्रक्रिया को रद्द करने का अधिकार अद्योहस्ताक्षरकर्ता को होगा। निविदा से सम्बन्धित अन्य शर्तें एवं जानकारी कार्यालय से कार्यालय समय में प्राप्त की जा सकती है।

प्राचार्य
अभियांत्रिकी महाविद्यालय
धौलपुर

Brajesh

Bijay

Milish chah

Kishor
TO

Prakash

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

अपेक्षित दस्तावेज एवं चेक लिस्ट -

Sr.No.	Particulars	Enclosed (Yes/No)	PageNo
1.	D.D. for Bid Fees, Bid Security and RISL Processing Fees		
2.	The bidder shall have Minimum Average Annual Turnover of Rs 45.00 lacs during last three Financial Years i.e. 2023-24, 2024-25 and 2025-26. Net worth shall be positive as per audited accounts of bidder/firm on 31.03.2025. Regarding average annual turnover of last three Financial years Bidders shall submit Auditors Report/CA Certificates along with Bid.		
3.	During last five years period, the Bidder Shall have successfully completed similar nature of work of cumulative value of minimum Rs 51.00 lacs or more in all over India (any state & UT). The bidder shall provide & append copies of work order and submit certificates regarding successful completion of above said work.		
4.	Self attested copy of PAN card.		
5.	Self-attested copy of Goods and Service Tax registration and copy of latest GST return (Not older than four months) filed shall be enclosed.		
6.	Self attested Copy of firm's registration under Proprietorship/ Indian Partnership Act, 1932/ Indian Companies Act, 1956/Societies Registration Act, Cooperative Societies Act along with copy of bye laws be submitted with relevant authority in India or any other Act of State/ Union, as applicable for dealing in the subject matter of procurement.		
7.	If the bidder is MSME, in this regard they shall submit relevant forms, certificates and affidavit for applicability.		
8.	Annexure-A: Compliance with the code of integrity and no Conflict of Interest		
9.	Annexure-B: Declaration by the Bidder regarding Qualifications		
10.	Annexure-C: Grievance Redressal during Procurement Process		
11.	Annexure-D: Additional Conditions of Contract		
12.	Annexure-E: Annual Turnover Statement (duly certified and signed by Chartered Accountant)		
13.	Annexure-F: Statement of Past Work Experience and Performance		
14.	Annexure-G: Declaration regarding acceptance of Terms & Conditions of Bid		
15.	Annexure-H: Manufacturer's Authorization Form (MAF)		
16.	Annexure-I: Bidder's Authorization Certificate		
17.	Annexure-J: Certificate regarding Non Black listed		
18.	Annexure-K: Certificate of Conformity/No Deviation		
19.	Annexure-L: UNDERTAKING ON AUTHENTICITY OF EQUIPMENTS		
20.	Annexure-K: Bid Security Declaration in pursuant to the Circular No.पं. २(१)वित्त./जीएण्डटी-एसपीएफसी/2017 दिनांक 23.12.2020 of finance (G&T) department jaipur, Rajasthan		

Handwritten signature and initials

Handwritten signature

Handwritten signature

Handwritten signature: millesh chudas

Handwritten signature: Vishnu

Handwritten signature: Brajesh

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

Civil Engineering Department Lab की आपूर्ति,

स्थापना एवं कर्मिशनिंग हेतु खुली निविदा

Pre-Qualification/Eligibility Criteria:

1. बोलीदाता की फर्म अधिकृत पंजीयन अधिकारी से पंजीकृत एवं यथा आवश्यक संबंधित सामग्री के व्यापार का वैध लाईसेंस होनी चाहिए जिसके संबंध में फर्म का पंजीयन प्रमाण पत्र निविदा के साथ संलग्न प्रस्तुत किया जावे।
2. GST पंजीयन संख्या का प्रमाण पत्र स्वयं द्वारा प्रमाणित प्रति निविदा के संलग्न प्रस्तुत किया जावे।
3. बोली शुल्क एवं बोली प्रतिभूति राशि के D.D. निविदा में प्रस्तुत करने की अन्तिम दिनांक तक कार्यालय में व्यक्तिश अथवा डाक द्वारा प्राप्त हो जाने चाहिये अन्यथा तकनीकी स्तर पर ही निविदा निरस्त कर दी जायेगी।
4. आयकर विभाग द्वारा जारी पैन नम्बर की प्रमाणित प्रति निविदा के संलग्न प्रस्तुत किया जावे।
5. फर्म का गत 03 वित्तीय वर्षों (वर्ष 2023-24 से 2025-26) का कुल औसत वार्षिक वित्तीय टर्नओवर राशि रूपए 45.00 लाख से कम का नहीं होना चाहिये। वित्तीय टर्न ऑवर के संबंध में सी.ए. द्वारा ऑडिटेड विवरण पत्र /बैंक शीट/सी.ए. सर्टिफिकेट की स्वहस्ताक्षरित प्रति स्केन कर बोली दस्तावेजों के साथ निर्धारित दिनांक तक अपलोड करने होंगे। फर्म की नेट वर्थ पॉजिटिव होनी चाहिए।
6. विगत 5 वर्षों में फर्म को केन्द्र/राज्य के किसी भी राजकीय विभाग/उपक्रम/स्वायत संस्थाए/परियोजनाए/ बोर्ड/ समिति / आयोग/ शिक्षण संस्था/बैंको/आदि में कुल 51.00 लाख रु. या उससे अधिक मूल्य की समान प्रकृति की सामग्री की सफलतापूर्वक आपूर्ति का अनुभव होना आवश्यक है। इस हेतु फर्म द्वारा क्रयादेश अथवा संतोषजनक कार्य के प्रमाण पत्र की प्रति निविदा के साथ संलग्न प्रस्तुत किया जावे।
7. क्रय की जाने वाली सामग्री के नमूने के रूप में सामग्री के कैटलॉग मय स्पेशिफिकेशन के तकनीकी बोली के साथ प्रस्तुत किये जावे। बोलीदाता द्वारा प्रस्तुत कैटलॉग मय स्पेशिफिकेशन बोली में चाहे अनुसार होने चाहिए अन्यथा तकनीकी बोली स्वीकार नहीं की जावेगी। कैटलॉग का अवलोकन उपापन समिति/तकनीकी समिति द्वारा किया जायेगा। बोली में सफल बोलीदाता द्वारा सामग्री की आपूर्ति के समय नमूनों को उपापन समिति/तकनीकी समिति से अनुमोदित करवाना होगा।
8. नवीनतम जी.एस.टी. रिटर्न/चुकता प्रमाण पत्र संलग्न करना होगा।
9. तकनीकी बोली के साथ बोली के साथ यथा संलग्न प्रपत्र/एनेक्सर ए से के तक प्रमाणित कर प्रस्तुत करने होंगे।

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

10. बोलीदाता केन्द्र/राज्य के किसी भी राजकीय विभाग/उपक्रम/स्वायत्त संस्थाए/परियोजनाए/बोर्ड/समिति /आयोग/षिक्षण संस्था/बैंको/आदि के द्वारा ब्लैक लिस्टेड अथवा डि-बार किया हुआ नहीं होना चाहिए। इस हेतु बोलीदाता को नॉनज्यूडिशियल स्टाम्प पर शपथ पत्र देना होगा। यदि शपथ पत्र गलत पाया जाता है तो उस बोलीदाता की बोली पर विचार नहीं किया जावेगा।
11. बोलीदाता द्वारा वित्तीय बोली /प्राईस बिड को छोडकर शेष बोली दस्तावेजों को बोलीदाता के सम्बन्धित प्रमाण पत्र एवं कागजात के साथ तकनीकी बोली /क्वालिफाईड बिड के साथ प्रस्तुत करना है। वित्तीय बोली /प्राईस बिड पृथक से वित्तीय बोली प्रपत्र में भरकर अलग लिफाफे में जमा कराना है।
12. उक्त पात्रता पूरी करने वाले योग्य निविदादाता तकनीकी बोली में (प्री क्वालिफिकेशन से) सफल माने जायेंगे एवं तकनीकी बोली में सफल बोलीदाताओं की ही वित्तीय बोली खोली जायेगी।

दिनांक:

बोलीदाता के हस्ताक्षर मय सील

~~खोला~~
To Byp

B192

2

mitalchats

1/11/2011

Brajesh

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

Civil Engineering Department Lab Equipments की आपूर्ति, स्थापना एवं कर्मिंशनिंग हेतु खुली निविदा

तकनीकी बोली प्रपत्र

क्र.स.	विवरण	बोलीदाता द्वारा की जानेवाली कार्यवाही	संलग्न है / नहीं (पेज संख्या)
1	बोलीदाता/फर्म/संस्था का नाम	
2	बोलीदाता/फर्म/संस्था का पता मय मोबाईल नम्बर/ई-मेल पता मोबाईल नम्बर..... ई-मेल	
3	बिड सूचना क्रमांक व दिनांक / 2026-27 दिनांक.....	
4	बिड की अनुमानित लागत	रु. / -	
6	बिड प्रस्तुत करने की अन्तिम तिथि व समय	दिनांक समय:- पीएम	
7	तकनीकी बोली खोलने की दिनांक व समय	दिनांक समय:- पीएम	
8	बोली प्रपत्र शुल्क राशि रु 500 / - D.D.	DD No. Date :-	
9	बोली प्रतिभूति राशि (अनुमानित राशि का 2 प्रतिशत) रु..... / -	DD No. Date :-	
10	RISL Fees रु 1500 / - D.D. द्वारा	DD No. Date :-	
11	फर्म का जीएसटी रजिस्ट्रेशन नम्बर (प्रति संलग्न करें)		
12	फर्म का पेन कार्ड नम्बर (प्रति संलग्न करें)		
13	बैंक का नाम एवं बैंक खाता संख्या मय आईएफएससी कोड	बैंक का नाम.....खाता संख्या..... आईएफएससी कोड.....	
14	गत तीन वर्षों का औसत टर्नओवर राशि रु 45.00 लाख रु. (वर्ष 2023-24, 2024-25 एवं 2025-26) सी.ए. द्वारा प्रमाणित, (प्रति संलग्न करें मय यूडीएन नं०)	औसत टर्नओवर..... (सीए द्वारा प्रमाणित) (प्रति संलग्न है)	
15	गत 5 वित्तीय वर्ष में केन्द्र/राज्य के राजकीय विभाग/उपक्रम/स्वा०	क्रयादेश एवं संतोषजनक कार्य संपादन का प्रमाण पत्र की प्रति संलग्न करें।	

Prakash *Prakash* *Bilgits* *राजीव*
mital chub *CO RHP*

	संस्थाए/परियोजना/बोर्ड/समिति/आयुग/शिक्षण संस्था/बैंको में कुल 51.00 लाख रू. या अधिक संबंधित सामग्रीआपूर्ति कराये जाने का प्रमाण पत्र ।		
16	अपेक्षित दस्तावेज एवं चैक लिस्ट के अनुसार सभी एनेक्सर एवं अन्य आवश्यक दस्तावेज ।	संलग्न है।	
17	बिड के साथ संलग्न किये गये सभी शर्तों पर शर्त स्वीकार किये जाने हेतु बोली दाता द्वारा हस्ताक्षर कर दिये गये है।	संलग्न है।	

नोट:-

1. बोलीदाता फर्म पार्टनरशिप फर्म होने की स्थिति पर साझेदारी बिलेख तथा कम्पनी की स्थिति में कम्पनी ऑफ रजिस्ट्रार का प्रमाणित विलेख/दस्तावेज संलग्न करें।
2. फर्म के परिसर/दुकान/कार्यशाला/गोदाम का सही पता जिस का आवश्यकता होने पर उपापन समिति द्वारा निरीक्षण किया जा सके।
3. उपापन समिति/जिला कलक्टर बोली की किसी भी शर्त को किसी भी स्तर पर संशोधन करने/हटाने अथवा नई शर्त जोड़ने के लिए स्वतंत्र होगा।
4. क्रयादेश जारी करने के दिनांक से 40 दिवस की अवधि के भीतर फर्म द्वारा सामग्री की आपूर्ति, स्थापना एवं कमिंशनिंग करनी होगी। निर्धारित समय तक आपूर्ति नहीं करने पर परिसमापित नुकसानी की नियमानुसार कटौती की जा सकती है।
5. मैं/हम, निविदा सूचना एवं इस प्रपत्र में दी गयी सभी शर्तों से सहमत हूँ/है। इसके सभी पृष्ठों पर उल्लिखित शर्तों को हमारे द्वारा स्वीकार किये जाने के प्रमाण में मैंने/हमने हस्ताक्षर किये है। हम राज्य सरकार के उपापन संबंधी अधिनियम/नियम आदेश से आबद्ध होना स्वीकार करते है। यदि मेरे द्वारा प्रस्तुत कोई तथ्य गलत/मिथ्यापूर्ण पाया जाता है तो मैं उसके लिए पूर्ण रूप से जिम्मेदार रहूंगा।

(बोलीदाता के हस्ताक्षर)
मय सील

सतीश
10/04/20

10/04/20

10/04/20

Milok chub

10/04/20

10/04/20

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

1. बोलीदाता से संबंधित सूचनाएं-

(बिड संख्या -.....)

Sr.No.	DETAILS			
1	Name of Bidder			
2	Business Category: (pl tick)	Corporation	Individual	Sole Proprietorship
		Partnership	Limited Liability Partnership	Other, Pl Specify
3	Registration Number of Firm/Company (Also attach relevant certificate)			
4	Address of Correspondence			
5	Mobile No.			
6	GST NO.			
7	PAN NO.			
8	E-Mail Address			
9	BANK DETAILS OF BIDDER		Banker's name	
			Branch	
			Account type	
			Account number/IFS Code	
10	Name of Authorised Signatory			
11	Mobile No. of Authorised Signatory			
12	E-mail ID of Authorised Signatory			
13	Whether Bidder is a Manufacturer or Authorised Dealer, if Bidder is a Authorised Dealer then Name of Brand/Brands			
14	Any other Details			
	Name _____		Signature of the Bidder with Seal	

* Attach separate sheet for details, where required. In case of authorized representative signing this document enclose copy of the authority letter.

Vishwanath

Miloh chub

Brajesh

Kishor

Balraj

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

Civil Engineering Department Lab Equipments के तकनीकी स्पेशिफिकेशन-

A- Civil Engineering Material Lab

S. No.	NAME OF ITEM	SPECIFIC-ATION	QT Y.	Make/ Trade/ Mark/Brand/Modal	Compliances Yes/ No
1	VICAT NEEDLE APPARATUS	Vicat Needle apparatus for testing cement IS 4031, 264s,2542(PART-1), 1727,5513 Specification: The apparatus consists of a metallic frame bearing a freely movable and with a cap at top, one vicat mould and glass base plate and one set of needles one each initial needle, final needle and consistency plunger	05		
2	LE-CHATELIER MOULD	Le-Chatelier Mould IS: 269:4031 (set of six mould): With two glass plate and lead weight. For indicating soundness of cement and limes. A brass cylinder mould split down one side, and provided with two parallel indicating arms.	05		
3	PYCNOMETER	As Per IS 2386 (P-III) Specification : Specific Gravity is the ratio of the weight in air of a given volume of a material at a standard temperature to the weight in air of an equal volume of distilled water at the same stated temperature. The Pycnometer Bottle can be used to test a wide range of Materials from clay to sand and gravel smaller than 10mm. It consists of 1kg Glass Jar with Brass Cone, Locking Ring and Rubber Seal. Certification Required : ISO , GMP	05		
4	SLUMP TEST APPARATUS	Slump Test Apparatus with light base. The slump cone is made of heavy gauge steel sheet. The handles and foot clamps are welded in position. All parts are painted to resist rust. Made in form of frustum of a cone with 20 cm diameter open base and 10 cm diameter open top, height is 30 cm. complete with tamping rod 16mm dia x 600mm long. Certification Required : ISO , GMP	05		
5	COMPRESSION TESTING MACHINE	Supply Of Compression Testing Machine Mark Conforming to IS Code: 14828-2000 Compression Testing Machine for Concrete Cube & Cylinders Capacity 2000 KN, DIGITAL Model. It is an electrically operated machine for conducting compression tests on concrete Specimens up to 20cm dia and 30 cm in height. The Machine meets the essential Requirements of various Indian, British & American standard for compression tests. Loading Unit: The hydraulic jack of 2000kN capacity is fixed to base. Holding plates size is suitable to hold bricks and mould 1-28cm. Certification required: must enclose with bid Master Standard report of mode pattern of fracture at 1400KN, ISO, CE, GMP. The Upper platen has got a self-aligning action and is attached to a screw which passes through the cross head and can be raised or lowered for initial clearance adjustment. The lower platen rests on the jack ram and is positioned with the help of a centering pin. Loading is accomplished by the upward movement of the lower platen. Supplied with measurement device having big size display, meter should be phone size	01		

Handwritten signature
To Bhp

Handwritten signature
Btgs 3

Handwritten signature

Handwritten signature
Mishra

Handwritten signature
Kishan

Handwritten signature
Brijesh

		design with voltage alert alarm with flashlight. Capable for measure the freq. and voltage Pumping Unit: The motorized pumping unit which is housed in an Elegant console is of double plunger type and is driven by single phase 220 volts 50 cycles electric motor. The pumping unit is separate unit connected to the jack by means of a steel connecting tube. A junction box is suitably fixed to connect the motor to the mains through a push button starter. The pumping unit is fitted with Digital Indicator. The electric pumping unit is fixed with a micro-switch off the motor automatically as the load on the machine approaches the rated capacity. Relays are also incorporated in the pumping unit so that in the case of break- down of power supply, the motor will stop and would not-re-start unless starting switch is operated. NABL Calibration Certificate Should be Provided Along With Machine			
6	COMPACTION FACTOR TEST APPARATUS	IS 1199, 5515 & BS 1881-103 Specification: It consists of two rigid conical hoppers and a cylinder are fitted with hinged trapdoor having a quick release catches. A circular metal plate is provided to cover the top of the cylinder. Supplied complete with one plaster's trowel and one tamping rod, 16mm dia x 600mm long both ends rounded. Certification : ISO , GMP,CE	01		
7	CONCRETE MIXTURE MOTORIZED	Small size with Two wheel trolley based same as construction machine Certification : ISO , GMP,CE	01		
8	SHRINKAGE LIMIT APPARATUS	Conforming to the tolerance and specification in accordance to I.S.2720 part-vii for the determination of the water content level after which any further reduction in the water content will not cause a corresponding decrease in the volume of the soil mass. It consists of: Porcelain evaporating dish approx.. 12cm dia, Shrinkage dish of monal metal 45mm internal dia x 15mm high, Glass cup 50 to 55 mm dia x 25mm. deep, Perspex prong plate with tree metal prong. perspex plate plain 75 mm square, Spatula 20 mm width 80mm . long made of stainless steel with wooden handle, Glass measuring cylinder 25ml x0.5ml. Graduation WITHOUT OF MERCURY. Certification : ISO , GMP,CE	01		
9	FLOW TABLE	FLOW TABLE (Hand Operated) IS-5512: This is used for measuring I the consistency of pozzolanas and also cements mortar and hydrated lime. It consists of a machined table top 250mm 2.5mm dia mounted on a rigid stand. The table top is reinforced with equally disposed ribs and allowed to drop 12.5mm by a shaft. The cam is operated by hand. Supplied complete with on conical mould 100 min base dia. 70mm. top dia. 50 mm high.	01		
10	SIEVE SET	Sieve must be provided as per ASTM Standards, ISO certification required <ul style="list-style-type: none"> • IS Sieve for fine aggregate, brass frame 20 cm dia, set of 7 with lid and pan • IS sieve for coarse aggregate, GI frame 30 cm dia, set of 10 with lid and pan • Set of sieve provided with standard aggregate sizes with proper difference • Sieve no : 8,12,22,24,44,66,80 Certification : ISO , GMP,CE	18		
11	BUOYANCY BALANCE WITH DENSITY BASKET	Specific Gravity & Water Absorption of aggregates REFERENCE STANDARD: (PART II) & BS 812. This Set Is Used For Specific Gravity Apparatus Specific Gravity And Water Absorption Of Aggregates.	01		

Handwritten signature

Handwritten signature
Handwritten signature

Handwritten signature
TO ASHP

		<p>Specification: The outfit comprises of A Digital Weight Machine is a gadget to measure weight. It is equipped with highly accurate sensors to provide the exact reading in place of traditional weighing scales. A digital weight machine is the most accurate and precise device with an analogue front-end (AFE) force sensor to measure the load of any kind of mass or object. Certifications – bidder must enclose along with bid ISO, UL, GMP, FCC, ROHS, CMMI, and CE. A digital weight machine works on two basic principles that can be understood by splitting it into two parts, the first one is a sensor and another one is processing. The sensor part is known as load-cells that measures the weight and transfigures it into an electrical format. Then after the processing part receives the signal and displays it on the LCD screen in readout form. In simple words, a digital weight machine first calculates the mass weight in machine language Newton then converts and displays the weight into kilograms which is an easy-to-understand and readable format for the common man.</p> <ol style="list-style-type: none"> 1. Range 5 Kg 2. Least count 0.1 gms 3. Special Feature: not in use 4. Display Type: DCL 5. Weight Limit: 5 Kg 6. Form Factor: Mini 7. Material: Plastic 8. Readout Accuracy - 0.1 Grams 9. Weight Scale Type - Counter Scale 10. Measurement Type - g 11. Capable for measure the frequency and voltage. <ol style="list-style-type: none"> 2. Density basket. 3. Air tight container to suspend 4. GI Tray of area not less than 650 cm sq. 5. Absorbent cloths 75cm x 45cm 6. Supplied with measurement device having big size display, meter <p>Should be phone size design with voltage alert alarm with flashlight. Capable for measure the frequency and voltage. NABL Certificate Should be Provided Along With Machine</p>			
12	OVEN	<p>Digital microprocessor based Hot Air Oven Internal circuit wiring as per CE Norms</p> <ul style="list-style-type: none"> • 65mm high density Glass wool insulation on all sides to offer minimum chamber heat loss • Oven is fitted with heating elements on all three sides, ensuring uniform temperature distribution throughout the working chamber • Sealed and enclosed heater to working chamber for minimum heat loss • Microprocessor based Auto tune - PID Digital temperature indicator cum controller • 80/20 Ni-chrome heating elements, ensuring long lasting and continuous heating within the chamber • Special heavy duty Stainless steel lock and door hinges with spring and roller mechanism • Stainless steel crimped wire mesh Shelves to withstand heavy load and to offer minimum resistance to air circulation for better heat distribution <p>Provision to add more shelves, as per requirement of test - Adjustable Shelves to place test samples or Glass wares of varying dimensions</p> <ul style="list-style-type: none"> • Adjustable air ventilation mounted at top/back side 	01		

Wider To Rev

Btgsh

FE

Mishra

Mishra

Brajesh

		<ul style="list-style-type: none"> • Certifications ISO 9001:2015, CE, ROHS,UL,EPR,FCC, ISO20000:1:2011 • Bidder must enclose with bid: Standard Temperature mapping Report at 250°C with 24 Hours data for inner chamber catalogue and compliance • Operation on 220/230 Volt, 50 Hz, Single phase, AC Supply • With built-in forced air circulation arrangement for uniform heat distribution inside the working chamber • Complete with pilot indicating lamps, 2 meter cord wire <ul style="list-style-type: none"> • Inner chamber : Made of Stainless Steel S.S.304- • Outer Chamber : Fabricated from CRC Material • Paint : Powder coating in attractive shades • No. of trays : 3 Nos. (Additional shelf at extra cost) • Temperature Range : 50°C to 350°C • DIGITAL with air circulation fan • SIZE-14"X14"X14" • CHAMBER-SS triple walled construction <p>NABL Certificate Should be Provided Along With Machine</p>			
13	Electronic Weight M/C	<p>Range : 200kg</p> <p>The Weighing Scale represents the pinnacle of accuracy and durability, tailored to meet the rigorous demands of both industrial and commercial environments. Weighing scale with a generous size of 16 * 16 inches, this weighing scale offers ample space for weighing various items, from bulk materials to products in commercial establishments. With a maximum weight capacity of 200kg lest count 10g, readability 1gm, body made of powder coated Mild steel sheet and top made of SS/MS/cast iron with superior quality finish. Certifications – bidder must enclose along with bid ISO, UL, GMP, FCC, ROHS, CMMI, and CE. Weighing scale provides versatility and reliability, ensuring precise measurements for a wide range of applications. Weighing scale crafted with robust materials and engineering, the Weighing Scale is built to withstand the heavy demands of industrial use. Its sturdy construction ensures stability and durability, even when dealing with large and heavy loads. Whether you're operating in a busy warehouse or a bustling retail store, this scale delivers consistent and accurate results every time. Designed for ease of use, the Weighing Scale features a user-friendly interface that simplifies operation for users of all skill levels. The clear and intuitive display of weighing scale makes it easy to read measurements, ensuring efficiency and reducing errors in weighing processes.</p> <p>NABL Certificate Should be Provided Along With Machine</p>	01		
14	ELECTRONIC WEIGHT M/C	<ul style="list-style-type: none"> • Range 30Kg • Least count 2 gm • A Digital Weight Machine is a gadget to measure weight. It is equipped with highly accurate sensors to provide the exact reading in place of traditional weighing scales. A digital weight machine is the most accurate and precise device with an analog front-end (AFE) force sensor to measure the load of any kind of mass or object. Certifications – bidder must enclose along with bid ISO, UL, GMP, FCC, ROHS, CMMI and CE. A digital weight machine works on two basic principles that can be understood by splitting it into two parts, the first one is a sensor and another one is processing. The sensor part is known as load-cells that measures the weight and transfigures it into an electrical format. Then after the processing part receives the signal and displays it on the LCD screen in 	01		

Handwritten signature

Biggs 13

Project

Handwritten signature

		<p>readout form. In simple words, a digital weight machine first calculates the mass weight in machine language Newton then converts and displays the weight into kilograms which is an easy-to-understand and readable format for the common man.</p> <p>NABL Certificate Should be Provided Along With Machine</p>		
15	ELECTRONIC WEIGHT M/C	<p>A Digital Weight Machine is a gadget to measure weight. It is equipped with highly accurate sensors to provide the exact reading in place of traditional weighing scales. A digital weight machine is the most accurate and precise device with an analogue front-end (AFE) force sensor to measure the load of any kind of mass or object. Certifications – bidder must enclose along with bid ISO, UL, GMP, FCC, ROHS, CMMI and CE. A digital weight machine works on two basic principles that can be understood by splitting it into two parts, the first one is a sensor and another one is processing. The sensor part is known as load-cells that measures the weight and transfigures it into an electrical format. Then after the processing part receives the signal and displays it on the LCD screen in readout form. In simple words, a digital weight machine first calculates the mass weight in machine language Newton then converts and displays the weight into kilograms which is an easy-to-understand and readable format for the common man.</p> <ul style="list-style-type: none"> • Range 6 Kg • Least count 0.1 gms • Special Feature: noticnuF eraT • Display Type: DCL • Weight Limit: smargoliK 6 • Form Factor: iniM • Material; Plastic • Readout Accuracy - 0.1 Grams • Weigh Scale Type - Counter Scale • Measurement Type – g <p>NABL Certificate Should be Provided Along With Machine</p>	01	
16	TROWEL	<p>Material : Carbon steel Handle material : Wooden</p>	01 Set	
17	CBR Test Machine	<p>As Per IS: 9669, IS 2720 (Part XVI) It is used in large road construction projects have increased considerably in recent years. This apparatus can be used to determine the bearing capacity of soils quickly and efficiency. This method of testing in-situ, using piston penetration, is useful for determining the load carrying capacity in the field, when the in-place density and water contents are such that the degree of saturation is 80% or greater. When the material is coarse grained and cohesion less so that it is not affected by changes in the water content and when the material has been in place. Similar to above but supplied with bench mounting type5000kgf. Capacity load frame motorized, in place of load frame hand operated. The lead screw of the load frame has a single constant rate of travel of 1.25mm/minute. Certifications required: ISO,CE,GMP,SA8000:2014</p> <p>Dial Gauge 25 mm in travel & 0.01mm in division for CBR penetration measurement, having provision for increasing the dial gauge- plunger length Proving ring, 50 kN (5,000kgf) capacity x 0.5. kN/Div sensitivity/ readability, one with 25 kN capacity x 0.04 kN/div sensitivity/readability and one with 10 kN capacity x 0.01 kN/div sensitivity/readability.\</p> <p>NABL Certificate Should be Provided Along With Machine Certification : ISO , GMP,CE</p>	01	
18	LOS ANGELES TESTING M/C	<p>Los Angeles abrasion testing machine with abrasive charge Supplied complete</p>	01	

*KT-101
To RHP*

Polgob

KE

Amlesh chandra

Hushmy

Brijesh

		Tray, Abrasive charge set of 12 hardened steel ball dia. 48 mm. Revolution counter meter, 50Hz frequency, stainless steel material, three phase NABL Certificate Should be Provided Along With Machine			
19	THICKNESS GAUGE	<ul style="list-style-type: none"> Used for determining the Flakiness Index of Aggregates. It Consists of 5 a frame with a sliding panel. The Panel has slots of Different Standard Lengths and Widths accurately Cut Size 145*70*27 mm Material: stainless steel <p>Thickness Gauge The Flakiness Index of Aggregates. Aggregates which are flaky and/or elongated will often lower the work ability of a concrete mix and may also affect Long Term Durability As Per Standard IS 2386 (PART-1) & BS 812. To check flakiness index and elongation index of the aggregate respectively. Accurate Measurement.</p> <p>Product Description: Thickness Gauge for Aggregate Is: 2386 (Part-I), Used for determining the flakiness index of aggregates. Featuring different standard lengths and accurately cut widths, these lightweight and accurately market gauges are reliable and easy to use. It consists of a frame with a sliding panel. The panel has slots of different standard Lengths and Widths accurately Cut in the IS 2386 (Part I)</p> <p>Certification : ISO , GMP</p>	05		
20	Length Gauge	<ol style="list-style-type: none"> Length Gauge Conforms to IS: 2386 (Part-1) Used for determination 5 of elongation index of aggregate. It is constructed of steel and is mounted on a hard wooden base. Size 30cm 8cm*8mm <p>Ensure the quality and reliability of construction materials with the Gauge with Length Gauge for Flakiness of Aggregate, a precision tool designed to measure the flakiness and elongation index of aggregates. This set is an essential part of any laboratory or field testing kit, enabling accurate determination of aggregate shape characteristics critical to the performance of construction materials. Certification required: ISO</p>	05		
21	LE-CHATELIER Flask	Used for finding specific gravity of hydraulic cement. Made from 5 Borosilicate glass. The long neck of the flask has at top a funnel of 50mm dia in that fits a ground glass stopper. The neck has over-all 11mm 1d. upper portion is graduated from 18ml to 24ml with 1 ml graduation. Just at the bottom of the neck 1 ml capacity is marked in between there is 17 ml capacity bulb. Glass material, 250ml capacity	05		
22	Marshal Stability test apparatus	<p>Marshall Apparatus Consists:</p> <p>Robust construction</p> <p>Safety cut-off switch</p> <p>Other Details:</p> <p>It consists of body housing, a geared screw jack and motor drive mechanism suitable for operation on 230 V,50Hz, Single Phase, AC supply</p> <p>Z1 4022-A: MARSHALL LOAD FRAME 1 No.</p> <p>Z1 4022-B: Breaking Head Stability Mould, with a dial gauge (having 25mm travel and 0.01mm least count), for flow measurement 1 No.</p> <p>Z1 4022-C Compaction Mould. Steel cylindrical 3 Nos</p> <p>Z14022-D. Base Plate 3 Nos</p> <p>Z1 4022-E Extension Collar 3 Nos.</p> <p>Z14022-F: Compaction Pedestal, Manual Operation, Comprising</p>	01		

Vishnu

nilakshya

Bilgish

Brujerh

Start to Ashp

		<p>a steel plate capped on a wooden post A Mould Clamp is fitted to the top of the plate 1 No. 21 4022-G: Compaction Hammer, satisfies BS 598. The hammer has a 4535 g sliding weight with a free fall of 457 mm 2. Nos. 21-4022-H Load Transfer Bar 1 No. 21 4022-1: Paper Discs, Non-absorbent, 11 cm diameter pack of 100 No. 1. Pkt Capacity 50 KN Certification : ISO , GMP,CE NABL Certificate Should be Provided Along With Machine</p>			
23	Ductility Testing Machine	<p>The apparatus consists of a Water bath with a thermostatic heater, and a 1 circulating pump to maintain uniform water temperature. One half of the briquette moulds is fixed on a fixed plate in the water bath, the other half of the briquette mould is fixed to a carrier which slides over a rotating threaded shaft with a clutch. The motor and gears to rotate the shaft are housed in a cabinet fixed above the other end of the bath. A pointer fixed to the carrier moves over a scale graduated from 0-110 cm x 1mm fixed on the bath with "0" (zero) of the scale towards the fixed plate side. The rotating shaft has 2 speeds of travel for the bracket, 3cm/min and 1 cm/min, selected by a clutch. Water bath inside is SS 304 grade, jacket insulated water bath. Water bath is provided with a drain. A heater with thermostatic control is fixed inside the water bath. Control switches for motor, stirrer, heater and indicator lamps are fixed at a convenient place on the water bath. Certifications: ISO,CE,GMP,FCC,ROHS,CMMI and standard temperature mapping report should be provided along with catalogue and compliance to ensure proper efficient design of heat temperature circulation, complete with three briquette moulds and one base plate, all made of brass. Operates on 230 volts A.C. single phase Salient The Features Machine TEST OF DUCTILITY consist of the APPARATUS following Stainless steel bath Temperature controller (Thermostatic/Digital) Immersion electric heater Constant speed pump cum stirrer Carriage holding up to three standard briquette moulds Electric motor with gear mechanism Stainless steel scale and pointer Control Panel Accessories: 1. Thermometer IP 38 C. range 23°C to 27°C. 2 Briquette mould with base-plate. NABL Certificate Should be Provided Along With Machine</p>	01		
24	Ring and Ball Apparatus	<p>The Ring and Ball Apparatus is a compact user-friendly apparatus. It has 1 magnetic stirrer with the heating facility and digital display of temperature, the heating can be adjusted through knob in AIM 561-1 and can be controlled through the integral PIO controlled in Ring and Ball Apparatus (Semi-Automatic) This apparatus is meant for the determination of the softening point of bituminous materials. Softening point is that the temperature at which the specimen under test becomes soft enough to allow a steel ball of specific dimension to fall a required distance under test condition, To determine the temperature at which sample of bituminous material loaded by 9.5mm dia steel ball drops from a specified distance when Heated under specified conditions.</p> <p>Features</p> <ul style="list-style-type: none"> • Real time display of temperature & time • Applicable for water and glycerol liquid • Adjustable speed magnetic stirrer for equally temperature control. • Auto display average lost result <p>Certification : ISO , GMP,CE NABL Certificate Should be Provided Along With Machine</p>	01		

B/gm

*K/akt
To RHP*

shim

M/est

Pr/dm

Br/urb

25	EXTRACTOR BITUMEN	This instrument is used for determination and checking of bitumen I percentage in bituminous mix, the mix is added with a Solvent and dissolved bitumen is removed by centrifugal action. Consists of a removable aluminium rotor bowl, capacity 3000gms. This shaft and thus the bowl is rotated fast manually by enclosed gears in the cast body and handle. Operates on 230volts A.C. single phase, Bowl capacity 1.5 ltr.	01		
26	Enamel Tray	SIZE-12" X18"	05		
27	Concrete Mixing Tray	Size 4 X 3 ft., 3 X 2' rectangular in shape, material mild steel, 4 handles	02 each size		
28	Sieve shaker	Sieve shaker is carry up to 7 sieves of 18-22 cm diameters. The shaker is driven by a % H.P. Electric motor. Efficiency: Saves time and effort in sample preparation. Accuracy: Provides high precision and repeatability in particle size analysis. Versatility: Suitable for a wide range of materials and applications. Timer and controller: manual analogue timer and rpm meter provided to set the rpm with marking Certified required: ISO,CE	01		
29	Shovel	Material iron, weight approximate 4 kg, length up to 3.25 ft. and corrosion resistance	05		
30	Measuring Cylinder	500 ml capacity, cylindrical in shape and plastic material	05		
31	Glass Beaker	65mm Diameter, 1000ml capacity, cylindrical in shape	05		
32	Lab wash Bottle	500ml capacity, screw cap, plastic material	05		
33	Blane Air Permeability Apparatus	For determining the fineness of cement in terms of specific surface area in square centimetres per gram of cement. This is a variable flow type air permeameter. The Apparatus consists one each of permeability cell 12.5 mm L.D., Manometer 'U' type mounted on stand with a built in stop cock, perforated disk, plunger rubber stopper, Rubber tube 30cm long. Packet of 12 filter paper discs and a bottle of 100cc dibutyiphthalate liquid. Fineness of cement has a great effect on the rate of hydration and hence the rate of gain of strength. Fineness of cement increases the rate of evolution of heat. Finer cement offers a great surface area for hydration and hence faster the development of strength. NABL Certificate Should be Provided Along With Machine	01		
34	Flexural Testing Machine	Electric Cum Digital Load Display (Leasé Count 1 kn), (Capacity 100 KN) 10 Ton Suitable for operation on 220V, 50Hz, Single Phase, AC supply. The Flexural Strength Testing Machines are designed to test flexural strength of concrete beams. For testing beams of Size: 100X100X500mmSize: 150X150X 700mm. Certification : ISO , GMP,CE NABL Certificate Should be Provided Along With Machine	01		
35	ULTRASONIC PULSE VELOCITY TESTER	ULTRASONIC PULSE VELOCITY TES Should be Features for Non-destructive testing (NDT) of concrete quality by Ultrasonic Pulse Velocity (UPV) measurement method. Applications include estimation of properties of concrete such as strength, uniformity, crack depths, etc. The instrument is designed to comply with the recommendations of BS EN12504-4:2004, ASTM C597-71 (re-approved 1979) and IS 13311(Part I); 1992. SPECIFICATIONS: Method of Measurement	01		

Mishra

Digsh
Brajesh
Mishra

KT
to Ashu

		<p>Ultrasonic Pulse Transmission time measurement with two probes (transducers) system. Time Measurement Ranges: 0.1-9999.9us Measurement Parameters: Velocity or Path length, Crack Depth estimation Measurable Path Length: Up to 5-6 meters in acceptable quality of concrete, but it could vary according to the quality of the concrete & material. Frequency of Transducers: Standard: 54 KHz. Operator Adjustments a. Calibration using Calibration rod b. Parameter Settings like Excitation Voltage & Sensitivity c. Continuous/Burst Measurement mode (Refer Manual for details.)</p> <ul style="list-style-type: none"> • Electric Power Source: Internal 3.7 VDC Li-ion Rechargeable battery. Or External 5 VDC/4 Amp adapter. Battery Operating Capacity: 6 Hrs Approx. • Power Consumption: 5 Watts • Operating Temperature Range: 0 to 50 °C. <p>Size Weight W-160 mm x H-66 mm x D-280 mm Main Instrument: 1.2Kg. 54KHz transducer: 900 Gm each x 2 nos. NABL Certificate Should be Provided Along With Machine Certification : ISO , GMP,CE</p>			
36	REBOUND HAMMER	<p>Includes: Digital hammer with USB cable cum charger, grinding stone, chalk, documentation and carrying case. Certification : ISO , GMP,CE</p>	01		
37	COCRETE CORE CUTTING MACHINE	<p>Portable concrete core cutter:- Specifications for Core drilling machine up to 150mm dia.</p> <ul style="list-style-type: none"> • Stainless steel drill stand with Weight not more than 17 kg Travel length: 600mm, Maximum diameter: 250 mm, The stand should be such that it can drill the core at an angle of 450., Motor quick release system (STS), Left and right ended operation Aluminium anchor-/vacuum base, Robust and rigid stainless steel column with brass sliding guided carriage, quick motor disconnect system(STS), angle device and Anchor vacuum base. Voltage 230 V, 50-6-Hz, Power-2.5 KW, Speed-300/520/1700 rpm, End Connection of Machine -1% "UNC-R1/2". The machine should be provided with 100 mm dia. 01 no, core bit and150 mm dia. 01 nos. core, bit. The effective length of core bit should not be less than 400 nmm. The machines should have water connection system in it. The entire set should be provided with 10 Ltr. Capacity manual pressurized water Containers.. <p>Certification : ISO , GMP,CE NABL Certificate Should be Provided Along With Machine</p> 	01		
38	Permeability Apparatus Confirming to IS3085 and DIN 1048	<p>Minimum 3 points for 150 x 150 x 150mm System for measuring water penetration water penetration in three concrete samples (15cm cubes) vendor should be supply complete with required compressor, constant pressure arrangement, tubing and leak proof clamping arrangement as per DIN 1048. Certification : ISO , GMP,CE</p>	01		
39	Crushing value apparatus	<p>Ref. Standard-IS: 9376 This apparatus is used for measuring resistance of an aggregate to crushing, as per IS:2386, (Part 4).</p>	01		
40	Aggregate Impact Tester	<p>It is for determining the aggregate Impact value and has been designed in accordance with IS:2386 (Part 4), IS:9377. The sturdy construction consists of a base and support columns to form a rigid frame work around the quick Release trigger mechanism to ensure an effective free fall of the hammer</p>	40		

Bgsb

TO Dept

Mitesh Chaturvedi

Prashant

Brijesh

		during test. The free fall can be adjusted through 380-5 mm. The hammer is provided with a locking arrangement			
41	Cube Mould	150mmx150mmx150mm MADE OF CAST IRON 70.6mm x 70.6mm x 70.6mm MADE OF MILD STEEL 100X100X500mm beam mould MADE OF MILD STEEL 150X150X 700mm beam mould MADE OF MILD STEEL NABL Certificate Should be Provided Along With Machine	10		
42	Concrete Vibrator Table	Driven Type: Motor Power: 1.0 HP Material: Mild Steel Max Weight: 200-400 kg Table Dimension: 50CMX50CM	01		
43	Cement Vibrating Machine	The machine is capable for compaction of cement mortar cubes as per IS: 4031 and designed as per Standard IS: 10080. The complete frame assembly consists of device to hold a 7.06 cm cube mould to feed the sample in the mould. The frequency of vibration is 12000 ± 400 R.P.M. Vibration per minute. Supplied complete with one 7.06 cm cube mould. Complete with One No. poking rod to meet IS: 10080 requirements.	01		
44	Standard Penetration Test	Technical Specifications Complete set up consists of the following individual parts & accessories. Detailed description of each part is given below : 1. Split spoon sampler (Head, Split barrel & shoe) : 1 No 2. Drive Monkey weight 63.5 kg : 1 No 3. Sampling drill A-rod 1.5 meter long : 3 No 4. Guide Pipe Assembly : 1 No 5. Tripod 5 meter long with pulley assembly : 1 No 6. Rope for hammer : 10 Meter Split Spoon Sampler : Consists of 3 main parts; head, split-barrel and shoe. The sampler is having 35mm Inner Diameter (I.D.) and 50mm Outer Diameter (O.D.). It is 650 mm long. The sampler is made from a sleek tube - split lengthwise and held together by a head fitted with a ball check valve. A hardened steel shoe of inside cutting edge of 35mm dia is also the part of assembly. One adaptor to connect 'A' type drill rods is Iso supplied with brass liner. Drive-weight assembly : Consisting of a 63.5 kg weight (hammer), a driving head (anvil) and a guide permitting free fall of 0.76 meter (76 cm) and an overlift capability of at least 100 mm. The lifting will be manual by manila rope and pulley. Sampling rod (A-Type drilling rod) : Steel A-rod is used to connect the sampler to the drive weight assembly. Drilling rod of 1.5 meter long will be supplied. Other sizes available at extra cost. Guide Pipe Assembly : Guide pipe assembly which is fitted with a driving head on one side having standard "A" drill rod thread & a cap on the second side. Drive weight falls freely through a height of 0.76meter (76 cm) Certification : ISO , GMP,CE Bidder Must Encloses With Technical Bid Standard IZOD Charpy Test Certificate Pipe Welding Joint.	01		
45	Standard unconfined compression apparatus	Standard unconfined compression apparatus must meet specific mechanical and measurement standards for accuracy. Loading Frame: Must have sufficient capacity, typically ranging from 2 kN to 50 kN. It must be strain-controlled to maintain a constant rate of movement. Strain Rates: Standard motorized units offer strain rates such	01		

Vishnu

Polgats
Milind Chatur

Brigida

Noted to RUP

		<p>as 1.25, 1.5, and 2.5 mm/min. Some advanced systems allow settings as low as 0.00003 mm/min.</p> <p>Measurement Devices:</p> <p>Load Measurement: Using a proving ring or digital load cell. For soils with UCS < 100 KPa, the load must be measurable to 1 KPa.</p> <p>Deformation Dial Gauge: Must have a least count of 0.01 mm and enough travel to permit at least 20% axial strain.</p> <p>Sample Dimensions:</p> <p>Soil: Minimum diameter of 38 mm with a height-to-diameter ratio of 2 to 2.5.</p> <p>Rock: Minimum diameter of 47 mm (or 10x the largest mineral grain) with a ratio of 2.0 to 2.5 (ASTM) or 2.5 to 3.0 (ISRM).</p> <p>Certification : ISO , GMP,CE</p>		
--	--	---	--	--

B- Fluid Mechanics Lab

1	Bernoulli's Theorem Apparatus	<p>To verify the Bernoulli's theorem. Bernoulli's Theorem Apparatus</p> <p>Specifications:</p> <ul style="list-style-type: none"> SS Tanks: 2 numbers of suitable size mounted on stand of size 150mm x 150mm x 450mm height. Flow channel of 900 mm length made out of Perspex sheets. Piezometer tubes equally spaced at 7.5 cm Measuring tank of 45 LIT CAPACITY. Stop clock. Sump tank of 100Liter capacity Range of Experiments: Bernoulli's theorem for the flow of real liquid can be verified. Hydraulic grade line & the total energy line along the flow section can be plotted & can be studied. <p>Certification : ISO , GMP,CE, SA 8000:2014</p>	01	
2	Venturi meter & Orifice meter Apparatus	<p>Objectives</p> <ul style="list-style-type: none"> To calibrate the Venturimeter. To calibrate the Orificemeter. Venturimeter & Orifice meter Apparatus <p>Specifications:</p> <ul style="list-style-type: none"> Sump tank with flow-80 liter capacity Measuring tank 55-45 lit capacity Mercury Manometers (Differential) Each line provided with flow control valve for setting of different flow rates. Pressure tubes of different pipe lines are connected to common manometer through cocks. Easy to operate and replacement of Venturimeter & Orifice meter. (bidder must enclose along with bid master calibration certificate of venturimeter ,ISO,CE, SA8000:2014.) Flow control valve at the end of each line assures full running of pipe. Differential manometer of 500 mm length with mercury. Accuracy 0.1 mm <p>Range of Experiments:</p> <ul style="list-style-type: none"> Calibration of Venturimeter Calibration of Orifice meter <p>Certification : ISO , GMP,CE, SA 8000:2014</p>	01	
3	Metacentric Height of Ship Model	<p>To determine Metacentric Height</p> <p>Metacentric Height of Ship Model</p> <p>Specifications:</p> <ul style="list-style-type: none"> SS. tank or size 50x50x40cm with drain plug 	01	

Polgats

Height To Ship

Miles ch...

Lu Shm

Project

		<ul style="list-style-type: none"> A hollow ship model with balancing weight. Circular weight 4 in numbers. A graduated are for measuring tilt angle. Ship size 380 mm x 250mm x 175 mm. height. <p>Range of Experiments:</p> <ul style="list-style-type: none"> Determination of Metacentric Height of a War Ship/Cargo Ship <p>Certification : ISO , GMP,CE, SA 8000:2014</p>			
4	Orifice & Mouthpiece Apparatus	<p>To determine C_{c2}, C_{v2} C_d of an orifice. To determine C_d of a mouthpiece. Orifice & Mouthpiece Apparatus</p> <p>Specifications:</p> <ul style="list-style-type: none"> Basic Set-up: This is the basic module required by all the experimental setups. Storage Tank: 130 liter capacity. SS Made Measuring Tank 65 liter capacity SS Made Collecting Tank: Size of the collecting Tank is 35 liter fitted with drain valve 1" size Mano meter Tube. With marking scale. Monoblock Pump: Monoblock 1 ph, A HP pump shall be provided with the setup which shall be mounted on the base plate. The connection for the test equipment is made by flexible Hose-pipe. <p>Equipment: The present equipment is a set-up used to study the performance of orifice meter & Mouth Piece. Range of Experiments: The apparatus is designed to measure the co-efficient of discharge of orifice & mouthpiece. Certification : ISO , GMP,CE, SA 8000:2014</p>	01		
5	Notch Apparatus	<p>To determine C_d of a V-notch. Notch Apparatus</p> <p>Specifications:</p> <ul style="list-style-type: none"> SS. storage tank (channel) of size 250 mm x 250 mm x 900 mm Length, fixing arrangement for interchangeable notches. Measuring tank of 50 liter capacity Sump Tank size 8300 mm x 300 mm X 500 mm. Set of 2 brass Notches: (As requirement extra provided with extra cost) <ol style="list-style-type: none"> Rectangular Notch 'V' Notch.90°C Digital watch <p>Range of Experiments:</p> <ul style="list-style-type: none"> To determine Co-efficient of discharge (Cd) through <ol style="list-style-type: none"> Rectangular Notch V Notch <p>Metal plates - Notches, Rectangular Notch, 45° V Notch & 60° 90° V Notch Certification : ISO , GMP,CE, SA 8000:2014</p>	01		
6	Viscosity Meter	<p>Power Supply :- 90 to 260 V AC 50/60 Hz Power consumption :- 150VA Output :- USB port Main Body Size :- 360 x 350 x 590 mm (maximum) Weight :- approx. 9 kg Settable Rotational Speed :- 0.1 to 200 rpm (number of configurable stages 290) Viscosity Measurement Accuracy :- ±1.0% (F.S.) Viscosity Reproducibility :- ±0.2% (F.S.) Temperature Detection Range :- -100 to +300°C Main Display Items: - Viscosity value, torque value, shear rate, shear stress, temperature, spindle, etc.</p>	01		

Vishnu, Rajesh, Anil Chelva, Anil, TO RHP

C-Hydraulics Engineering Lab

1	LOSSES IN PIPE FITTING	<p>To determine the minor losses.</p> <p>Losses in Pipe Fitting</p> <p>Specifications</p> <p>This is the basic module required by all the experimental setups.</p> <p>Storage Tank</p> <p>Sump Tank SS Size: 100 liter capacity</p> <p>Collecting Tank-</p> <p>The collecting Tank is 60 liter capacity fitted with drain valve "1"size. Manometer tube with calibrated list marking scale.</p> <p>Mono block. Pump:</p> <p>Mono block, 1ph, ½ HP pump shall be provided with the set-up which shall be mounted on the baseplate. The connection for the test equipment is made by flexible</p> <p>House pipe</p> <ul style="list-style-type: none"> • Differential manometer of 500mm length with mercury <p>Range of Experiments.</p> <p>The apparatus is designed to demonstrate the loss of head due to the following fittings</p> <ul style="list-style-type: none"> • Pipe Elbow <p>Sudden Contraction</p> <p>Sudden Expansion</p> <ul style="list-style-type: none"> • Pipe bends, <p>Certification : ISO , GMP,CE, SA 8000:2014</p>	01		
2	FRICTION FACTOR	<p>To determine the friction factor.</p> <p>Specifications:</p> <p>Three pipes: 15mm, 19 mm & 25mm 1. D. nominal diameters approximately connected in a common manifold.</p> <ul style="list-style-type: none"> • Pressure tapping at 2 m distance. • Supporting stand structure for the equipment. • Measuring tank with drain valve & gauge glass. • Differential manometer of 500 mm length with mercury. <p>Range of Experiments:</p> <ul style="list-style-type: none"> • To determine coefficient of friction for pipes. • To plot relation between pressure loss & flow rates for a particular pipe diameter. <p>Certification : ISO , GMP,CE, SA 8000:2014</p>	01		
3	IMPACT OF JET APPARATUS	<p>To verify the momentum equation.</p> <p>Jet on vanes apparatus (impact of jet)</p> <p>Impact of Jet Apparatus</p> <p>Specifications:</p> <ul style="list-style-type: none"> • 30 cm x 25 cm dia. Transparent cylinder mounted on a stand. • adjustable load screw mechanism & dead weight to measure the force. Sump Tank 70 liter capacity • Measuring tank-35 liter capacity with drain valve. • Two nozzles with inside section: Straight taper Curved taper • Any Two vanes of • Semi-circular vane with angle of deflection 180° • Horizontal flat vane angle of deflection 90° <p>Range of Experiments:</p> <ul style="list-style-type: none"> • To study the impact of jet on various types of vanes & to measure impact forces. <p>To find coefficient of impact.</p>	01		

Big 3

*Mika
to RHP*

Meharab

Ar

Wigam

Brayeh

		Certification : ISO , GMP,CE, SA 8000		
4	RED WOOD VISOMETER	To determine viscosity of a given fluid. SUPPLIED WITH RED WOOD VISOMETER WITH 4 pes thermometer Certification : ISO , GMP,CE, SA 8000:2014	01	

D- Material Testing Lab

1	UNIVERSAL TESTING MACHINE	Capacity: 400 KN, Digital To conduct the Tensile Test on a U.T.M. and determine ultimate tensile strength, percentage elongation for a steel specimen, with following attachment. Mechanical Extensometer, Mandrel set along with software compatibility with PC The mechanical extensometer has twin dial gauges with a set of gauge length varying from 30 to 120mm (30 to 90 and another one 90 to 120). The maximum extension measured is 3mm. The dial gauges are with a maximum travel of 5mm (i) Tensile test attachment (ii) Compression test attachment (iii) Transverse test attachment Certifications: ISO, CE,GMP NABL Calibration Test Certificate Should be Provided Along With Machine	01	
2	Brinell cum Rockwell Hardness Testing Machine	Brinell cum Rockwell Hardness Testing Machine This is a combined hardness testing machine used to measure hardness of metals & alloys of all kinds, hard or soft, whether round, flat or irregular in shapes. Rockwell & Brinell method is used for checking hardness on metals& alloys of all kinds Brinell hardness is also checked on non-ferrous materials like Cast-iron, Aluminium, etc. Automatic weight selection with automatic zero setting dial gauge. Rockwell test minor load is 10 kgf & major loads are 60,100,150kgf. Brinell test for major load is 187.5 & Rockwell hardness scales such as HRA, HRB, HRC, etc. Brinell hardness scale such as HB is obtained by using different types of indentors (Diamond/Ball). <ul style="list-style-type: none"> • Test Loads (Kgf) 60, 100, 150 (Rockwell) 187.5(Brinell) • Initial Loads (Kgf). 10 Standard Accessories 1.) Flat Table of 50 mm Dia. 1 No. 2.) Vee Table for Specimen -50 mm Dia. 1 No. 3.) Diamond Indentor 1 No. 4.) 1/16" Ball Indentor 1 No. 5.) Rockwell Hardness Test Block 1 No. 6.) Brinell Hardness Test Block 1 No. 7.) Instruction Manual 1 Book 8.) Brinell Microscope 1 No. Certifications- along with bid bidder must enclose standard Absorbency test certificate for eye piece of microscope lens, BIS, ISO, CE for microscope NABL Certificate Should be Provided Along With Machine	01	
3	IMPACT TESTING MACHINE	The pendulum Impact Tester, it is designed for conducting 1 Izod, Charpy test The Pendulum is mounted on antifriction bearings. t has two starting positions, the upper one for Charpy & the lower one for Izod testing. On release, the pendulum swings down to brake the specimen and the energy absorbed in doing so is measured as the difference between the heights of drop before rupture of the test specimen and is read from the maximum pointer position on the	01	

Milish chid

Prishun

Bilgsh,

Prishun

To Ship

		<p>dial scale There are two strikers and one combined support available for fitting in to the pendulum and on to the base of the machine for the Izod, Charpy test respectively, Changing from one striker to another is achieved simply by fixing the new striker into its position Charpy Test</p> <p>The charpy test piece rests on alloy steel support anvils, fitted on the base of the machine rigidly held in position by Allen screws. End stopper is provided for quickly and accurately locating the test piece centrally between the supports</p> <p>Izod Test</p> <p>The Izod test is clamped vertically in Izod support fitted on the base of the machine. The support is provided with a machined Vertical groove to suit the test piece size. The front clamp piece and the Allen screw enable clamping of the test piece in correct height with the help of Izod setting gauge supplied</p> <ul style="list-style-type: none"> • Maximum capacity 300J/168J • Minimum Scale Graduation 2J • Overall Size (Approx.) 1.1m x 0.45 m x 1.65 m (H) • Charpy Striker 1 No. • Izod Striker 1 No. • Charpy Test Specimen 1 No • Izod Test Specimen 1 No. <p>Instruction Manual 1 Book. NABL Certificate Should be Provided Along With Machine</p>			
4	Digital Fatigue Testing Machine	<p>Digital Fatigue Testing Machine</p> <p>This machine is used to test the fatigue strength of materials and to draw S-N diagram by research institutes, laboratories, material manufactures and various industries. This is a rotating beam type machine in which load is applied in reversed bending fashion. The standard 8 mm dia. specimen is held in special holders at its ends and loaded such that it experiences a uniform bending moment. The specimen is rotated at 4200 rpm by a motor. A complete cycle of reversed stresses in all fibres of the specimen is produced during each revolution. The bending moment is applied with a lever system and can be easily changed by moving a weight over the lever. Total number of revolutions at which the specimen fails are recorded by a Digital counter. An interlocking system puts off the motor at specimen failure. Supplied with measurement device having big size display,</p> <ol style="list-style-type: none"> 1. Light weight, compact size, simple design. 2. Table model, no need of foundation. 3. Simple lever system of changing load 4. Accurately calibrated as per IS 5075 5. Calibration in Nm available on request. <p>TECHNICAL SPECIFICATIONS</p> <ol style="list-style-type: none"> 1. Maximum Bending moment kg cm 200 2. Bending moment adjustable kg cm 25-200 3. Ranges 1-kg cm 25-125, -kg cm 125-200 4. Gripping dia of specimen min-12 5. Testing dia of specimen mm 8 6. Rotating speed rpm 4200 7. Accuracy of applied bending moment. 8. Digital counter No. of digits 8 9. Power required HP 0.5 <p>Certification : ISO , GMP, CE</p> <p>Bidder Must Enclosed Master Standard Specimen Report for Breaking Pattern. NABL Certificate Should be Provided Along With Machine</p>	01		
5	Digital Spring Testing	<p>Spring testing machines are used for quick and accurate testing of tension and compression springs. The machine comprises of two hard chrome plated columns with fine cut single screw with</p>	01		

Bldget

Atal
TO RUP

M. S. Chandra

R

Prashant

Pravish

	Machine	<p>hand wheel for manual loading and unloading arrangement. The machine uses a high precision load pressure cell for measurement of force. For displacement measurement, mechanical linear scale. Certifications- bidder must enclosed master standard Stiffness/Hardness test certificate of spring along with catalogue and compliance. ISO,CE</p> <p>Quick and accurate measurement.</p> <ul style="list-style-type: none"> • Maximum Capacity 20KN • Width between Columns 160 mm • Maximum Cross Head Travel 160 mm <p>NABL Certificate Should be Provided Along With Machine</p>			
6	Digital Torsion Testing Machine	<p>It is designed for conducting torsion and twist on various metal wires, tubes, sheet materials torque measurement is by digital dynamometer system.</p> <p>Torque can be applied to specimen by geared motor through gear box.</p> <p>The accuracy of torque indication is t1 of the true torque</p> <p>Max. Torque Capacity 50KGM</p> <p>Torsion Speed 1.5</p> <p>Clearance between Grips 0-420</p> <p>Grips for flat Specimens width mm2-8, 25</p> <p>Motor (400-440 V, 3 Phases & 50 Hz)v 0.5</p> <p>Bidder Must Enclosed Along With Technical Bid Report Master Standard Breaking Pattern.</p> <p>NABL Certificate Should be Provided Along With Machine</p>	01		
7	Modulus of Rapture	<p>A creep-testing machine measures the creep (the tendency of a material after being subjected to high levels of stress, e.g. high temperatures, to change its form in relation to time) of an object. It is a device that measures the alteration of a material after it has been put through different forms of stress. Creep machines are important to see how much strain (load) an object can handle under pressure, so engineers and researchers are able to determine what materials to use. The device generates a creep time-dependent curve by calculating the steady rate of creep in reference to the time it takes for the material to change. Creep machines are primarily used by engineers to determine the stability of a material and its behaviour when it is put through ordinary stresses.</p> <p>Material Compatibility: Lead and PP (polypropylene) flat specimens.</p> <ul style="list-style-type: none"> • Specimen Cross-Section: 2 x 5 mm. • Measured Length: 25 mm. • Temperature Range: Experiments possible at or below room temperature with the included conditioning box. <p>Certifications: ISO,CE NABL Certificate Should be Provided Along With Machine</p>	01		
8	Tri-axial shear Machine	<p>Classification :- Geotechnical Engineering / Soil Mechanics Testing</p> <p>Power Source :- 220V AC Mains</p> <p>Application :- Civil Engineering, Geotechnical Research, Mining</p> <p>Color :- Select (Varies, often Blue/Grey Frame)</p> <p>Feature :- Highly Efficient</p> <p>Usage :- Critical element in advanced foundation design, slope stability analysis, and liquefaction studies</p> <p>Temperature Range :- Ambient to 50 C Celsius (oC)</p> <p>Voltage :- 220 V Volt (v)</p> <p>Accuracy :- 100 % %</p> <p>Capacity :- 10 kN (standard); other capacities available Kg</p> <p>Frequency :- 50 Hz Hertz (HZ)</p> <p>Automation Grade :- Automatic</p> <p>Material :- Steel, Acrylic, Precision Electronics</p>	01		

Mishra

AK

Bhaskar

Bhaskar

Jitendra
CO SHIP

		<p>Measurement Range :- 0-10 kN</p> <p>Product Type :- Advanced Soil Strength Tester / Geotechnical Research Equipment</p> <p>Operate Method :- Automated Shearing: Sample is set up in the cell under confining pressure; the motor advances the ram at a precise, constant strain rate, and all parameters (load, displacement, pressure) are digitally recorded</p> <p>Core Components :- Load cell, displacement transducer, microprocessor controller, digital display, triaxial cell</p> <p>Equipment Materials :- Corrosion resistant stainless steel with powder coated frame</p> <p>Type :- Electronic Triaxial Shear Test Apparatus</p> <p>Display Type :- Digital Display</p> <p>Dimension (L*W*H) :- Approx. 850 x 600 x 1100 mm Millimeter (mm)</p> <p>Weight :- Approx. 80 kg Kilograms (kg)</p> <p>Certification : ISO , GMP, CE</p> <p>NABL Certificate Should be Provided Along With Machine</p>			
--	--	---	--	--	--

E-Surveying Lab

1.	Engineer's Survey Chains : 20Mts	<p>Feature :- Specification</p> <p>Total Length :- 20 meters (approx. 65.62 feet)</p> <p>Number of Links :- 100 links</p> <p>Length per Link :- 20 centimeters (0.2 meters or approx. 7.87 inches)</p> <p>Material :- Heavy-duty galvanized iron (GI) or mild steel wire, often zinc-coated for rust resistance</p> <p>Wire :- Thickness Typically 4mm to 6mm, depending on the manufacturer and intended use (e.g., standard vs. heavy quality)</p> <p>Handles Strong brass handles are provided at both ends</p> <p>Markings (Tallies) :- Brass tags (tallies) are usually fixed at every 5-meter length for quick reading</p> <p>Intermediate Markings :- Small brass rings are often provided at every meter length (except where tallies are attached)</p> <p>Accessories :- Usually includes 10 chaining arrows for marking points on the ground</p> <p>Standard :- Conforms to Indian Standards (IS) specifications, such as IS 1492</p> <p>Permissible Error :- The maximum permissible error is generally considered to be ± 5 mm</p>	05		
2.	Engineer's Survey Chains : 30Mts	Chain having 150 links, confirming to ISI Specifications, made of GS wire 8 SWG having strong Brass handles at the both ends & metallic allies at every two links, tied with Nylon Belt.	05		
3.	Ranging Rod: 3 Meters	Made of conduit pipe 20SWG of 31mm Dia, Alternately painted Orange & White. The bottom end of the Ranging Rod shall be fitted with well pointed solid MS shoe. The Rod is detachable in 3 Pieces & Packed in a nice cover.	10		
4.	Ranging Rod: 4 Meters	Made of conduit pipe 20SWG of 31mm Dia, Alternately painted Orange & White. The bottom end of the Ranging Rod shall be fitted with well pointed solid MS shoe. The Rod is detachable in 4 Pieces & Packed in a nice cover.	10		
5.	Cross Staff:	Cross Staff made of Aluminium with size of 100 mm X 100 05 mm X 50 mm having 5 mm depth cross slots, Nicely Polished Accurately machined divided in 4 equal squares complete with strong solid MS Pole-Dia 5/8".	05		
6.	Prismatic	Prismatic Compass, made of full brass and aluminium circle,	05		

Blogs 3

*KAAT
To Bly*

Makub

R

Wishu

Braych

	Compass:	accurately machine graduated to 0.5 degree with agate stone bearing fitted with automatic lifter, with sliding lenestic prism fitted with Red & Green filter glasses and reflecting mirror. Certification : ISO , GMP			
7.	Surveyor's Compass	Surveyor's Compass made off all brass with 2 folding sight vanes, fixed aluminium graduated dial, properly machine graduated to 0.5 degree, fitted with 2 cross bubbles placed in Leather cover Size: 100mm dia, With Telescopic Aluminium Tripod	05		
8.	Aluminium Levelling Staff:	Size 4 Mts	10		
9.	Aluminium Levelling Staff:	Size 5 Mts	05		
10.	Plane Table:	Made of well-seasoned pine wood, with highly polished strong batons at the back fitted with brass screws & washers. A strong circular Brass Plate is fitted at the Back of Plane table for clamping on the Highly Polished Teak wood tripod, fitted with strong. Accessories: (One Each) I. Alidade:- Made of Brass sheet, heavy, quality, be well edged and accurately graduated fitted with strong brass vanes on the ends, chromium plated, size 600mm II. Magnetic Compass: Rectangular Pattern, made of full Brass, Graduated with properly magnetized needle having agate stone bearing to rest free point, Nicely painted size 150 mm III. Engineer's Level(Spirit Level): Made of Brass size 150 mm IV. Plumbing Fork: Made out from Brass sheet heavy pattern, nicely spray painted V. Plumb Bob: Made of Brass, bright buff polished Canvas cover:- Made of Waterproof canvas for plane table board & Stand	05		
11.	Dumpy Level:	Provided with Aluminium Telescopic tripod stand of high quality. Bubble: The tubular bubble shall be so mounted that it is adjustable both parallel and in line of sight of the telescope with reflector. A Circular Bubble provided on the plain surface of the instrument for quick pre-levelling. Vernier: The Horizontal circle is provided with a vernier and setting knob for accurate alignment to an accuracy of 6 min. Gradient Adjustment: Instrument fitted with graduated drum should be adjusted for gradient or elevation and depression. Technical Data ➤ Stadia 1:100 ➤ Reading Direct (Erect) ➤ Telescope Length: 225 mm ➤ Bubble: 30 sec per 2 mm ➤ Horizontal Circle: 360 Degrees ➤ Vernier: 6 minutes ➤ Telescope Power: 25 x ➤ Objective: 40 mm Wooden/Plastic carrying Box to place the dumpy level and canvas cover to place the stand.	05		
12.	Transit Vernier Theodolite: bob	Invert image theodolite having accuracy of 20 seconds, with Optical Plummet & hook for plumb	03		
13.	Electronic Theodolite	Angular Accuracy: 5" Least count: 1" Magnification: 30x Objective aperture: 45mm,	01		

Mishra

[Signature]

Kishu Bhasin

[Signature]

[Signature]
To

		Minimum Focus: 1.35m Image: Erect, Angle measuring mode: Absolute encoder Tilt compensator: Yes, Compensating range +/-3 Display: Dual side. identical display with Alphanumeric keyboard, Power supply: Battery: 4xsinglethree (AAA) type dry battery Optical Plummet, Operating temperature: -20°C to +50°C Essential Accessories: Aluminium Telescopic Tripod 1no. (Complete with all standard accessories)			
14.	Fibber Tapes	30 Mts and 50 meter	05		
15.	Hammer	Half pound weight with Company Handle	05		
16.	Metallic pegs	Dia 18mm MS Rod of Length 15 cm to 30 cm	20		
17.	Wooden Pegs	60cm*5cm*5cm	30		
18.	Automatic Level	Having 24x Magnification, Accuracy +2mm Image Erect, Effective Objective Aperture 42mm, Min. Focus 0.4m, Field Of View 1deg. 20 minute, Multiplication Constant 100. Additive Constant 0, Compensator Range +15. Compensator setting Accuracy +0.6" including Tripod, Leveling Staff, Toolkit, Operation Manual, Carrying Case, Plum bob. NABL Certificate Should be Provided Along With Machine	05		
19.	Arrows	Made up of steel and of 400mm length. It is coming with two different type. it is made up of 4mm dia steel rod	30		
20.	Vernier Caliper	<ul style="list-style-type: none"> The slider moves only when the spring loaded thumb clamp is depressed. Can measure OD, ID, depth, and steps Supplied with viny1 holster in fitted carton. Measuring Range 0-150mm Accuracy: 0.05mm NABL Certificate Should be Provided Along With Machine	01		
21.	Digital Vernier Caliper	<ul style="list-style-type: none"> Precisely engineered Compact size Unmatched quality IP67dust/waterproof Resolution:0.02mm/0.0005" Button function: zero, on/off, mm/inch, ABS/REL., hold Battery Made of stainless steel NABL Certificate Should be Provided Along With Machine	02		
22.	Optical Square	An optical 90° prism for basic manual measurement of 90° angles.	05		
23.	Plumb Bob	Steel plumb bob	05		
24.	BRUNTON COMPASS:	Material: Stainless steel Packaging type: Wooden Box Size: 2.5 inch	05		
25.	ABNEY LEVEL:	30cm in size in metal approximate weight 2kg.	05		
26.	TANGENT CLINOMETE R:	Made of Brass and aluminium and 150mm with rack and pinion attachment	05		
27.	DUAL AXIS LASER BASED ELECTRONIC TOTAL STATION	Angle Measurement Accuracy- 2 Usage/Application - BUILDING SURVEY WORK Resolving Power - YES Magnification- 30X Distance Measurement - 2 SECOND ACCURACY Angle Measurement- 2 SECOND Battery Operation- GEB111 LEICA DUAL Botanical Name - ASI-ROBUST Circular Level - YES	01		

Bhagat

Mishra
To

Mishra

Mishra

Mishra

Brajesh

	Color - OFF WHITE Compensation - DUAL AXIS Data Storage - 32 GB Data transfer - Bluetooth , pen drive and data cable Display - DUAL SIDE Display Type - DOS Field Of View - YES Image - ERACT Keyboard - BOTH SIDE Laser range max. - 600 mtr. Length - YES Measuring Time - 0.2 SECOND TIME Minimum Focus - 1.5 MTR Prism EDM Accuracy - 2MM+2PPM Prism EDM Range - 600MTR Range - 50000 Tile Angle Compensation - 2SEC Wireless Communication - BLUETOOTH Certifications: ISO,CE, GMP			
--	---	--	--	--

Special Terms & Condition

1. After installation of the equipment in the college campus minimum 5 day demonstration of working of equipment along with training to the laboratory officials is to be provided in the college laboratories.
2. All practical manual must be provided for each and every equipment.
3. All required certification and technical reports must be enclosed along with technical bid, otherwise bidder himself responsible for disqualification.

Mikeslath
VuShun
Biggs,
Brnich
 29
Krish To

कार्यालय, प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर

बोली से संबंधित सामान्य शर्तें—

(निर्देश— बोलीदाताओं को इन शर्तों को सावधानी पूर्वक पढ़ना चाहिए तथा अपनी ई-बोलियां भेजते समय इनकी पूर्ण रूपेण पालना करनी चाहिए।)

1. निविदादाताओं को निविदा में दिये गये निर्देशों के अनुसार निर्धारित प्रपत्र में उचित रूप से तकनीकी एवं वित्तीय बोली अलग-अलग निर्धारित प्रारूप में प्रस्तुत की जानी होगी। तकनीकी रूप से सफल बोलीदाताओं की ही वित्तीय बोली खोली जावेगी। तकनीकी रूप से अस्वीकृत बोली पर विचार नहीं किया जावेगा।
2. निर्धारित तिथि व समय के पश्चात प्राप्त बोली स्वीकार नहीं की जावेगी।
3. बोली शर्त रहित एवं बोली दर समस्त कर सहित दें।
4. उक्त बोलियों को आंशिक या पूर्ण रूप से स्वीकार/अस्वीकार करने का पूर्ण अधिकार प्राचार्य, राजकीय अभियांत्रिकी महाविद्यालय, धौलपुर को होगा।
5. बोली में आमंत्रित दरें अनुमोदित किये जाने की दिनांक से एक वर्ष की अवधि के लिये विधिमाम्य होगी तथा पारस्परिक सहमति से इस अवधि को नियमानुसार बढ़ाया जा सकता है।
6. फर्म का जी.एस.टी. रजिस्ट्रेशन होना आवश्यक है। इस सन्दर्भ में बोलीदाता को बोली प्रपत्र के साथ स्वयं हस्ताक्षरित जी.एस.टी. रजिस्ट्रेशन प्रमाण-पत्र की प्रति प्रस्तुत करनी होगी।
7. बोलीदाता बोली भरने से पूर्व अपेक्षित समस्त अर्हताओं एवं दस्तावेजों को स्वयं सत्यापन कर समाधान कर ले कि वह इस बोली हेतु समस्त पात्रताएं पूर्ण करता है। किसी भी स्तर पर गलत सूचनाएं, मिथ्या दस्तावेज आदि पाए जाने पर बोली अस्वीकार कर दी जाएगी एवं बोलीदाता के विरुद्ध जो भी कार्यवाही नियमानुसार होगी, की जाएगी।
8. निविदादाता द्वारा बोली प्रपत्र शुल्क जमा की विभागीय प्रति/रसीद तकनीकी बोली लिफाफे में संलग्न करना होगा। बोली प्रपत्र शुल्क किसी भी स्थिति में नहीं लौटाया जाएगा।
9. बोलीदाता द्वारा बोली प्रतिभूति शुल्क के स्थान पर बोली प्रतिभूति घोषणा पत्र वित्त विभाग के नियमानुसार निर्धारित प्रारूप Annexure-M में 50/- रु. स्टाम्प एवं उस पर देय सरचार्ज सहित हस्ताक्षर कर तकनीकी बोली के साथ संलग्न करना होगा। बोलीदाता आर.टी.पी.पी. नियम 42 में वर्णित प्रावधानों के तहत भी बोली प्रतिभूति शुल्क जमा करा सकते हैं।
10. MSME बोलीदाता को बोली प्रतिभूति/कार्य सम्पादन प्रतिभूति राशि में छूट प्राप्त करने के लिये वित्त विभाग द्वारा जारी अधिसूचना दिनांक 19.11.2015 एवं संशोधन दिनांक 29.08.2018 के अनुसार संबंधित दस्तावेज प्रस्तुत किया जाना अनिवार्य है, अन्यथा बोली प्रतिभूति/कार्य सम्पादन प्रतिभूति राशि में छूट देय नहीं होगी।
11. सामान/वस्तु की क्रय राशि अनुमानित है। अनुबन्ध अवधि के दौरान क्रय सामग्री की कुल क्रय अनुमानित कीमत से कम/अधिक हो सकती है। सामग्री का क्रय राज. लोक. उपापन में पारदर्शिता नियम 2013 के उपनियम 73 के अनुसार किया जा सकेगा।
12. बोलीदाता/प्रदायकर्ता द्वारा निविदा में वर्णित अनुसार एक आईटम की एक ही दर एवं मेक/मॉडल प्रस्तुत करेगा।
13. बोली प्रपत्र में अंकित शर्तों के अतिरिक्त किसी प्रकार की कोई शर्त अंकित न की जावे। सशर्त बोली स्वीकार नहीं की जावेगी।
14. बोली दस्तावेजों में परिवर्तन: बोली प्रस्तुत करने के लिए अन्तिम समय सीमा से पूर्व किसी भी समय उपापन संस्था किसी कारण से चाहे स्वप्रेरणा पर या बोली लगाने वाले के द्वारा स्पष्टीकरण के लिए किसी अनुरोध के परिणाम स्वरूप धारा 23 के उपबन्धों के अनुसार युक्तिका जारी करके बोली दस्तावेजों को उपान्तरित कर सकेगी।

- कार्यालय में उपस्थित होकर समाधान प्राप्त कर सकेगा।
16. बोलीदाता अपनी संविदा को या किसी सारवान भाग को किसी अन्य एजेन्सी के लिए नहीं सौंपेगा या उपभाडे पर नहीं देगा अर्थात् उसे सबलेट नहीं कर सकेगा।
 17. बोलीदाता या उसके प्रतिनिधि की ओर से प्रत्यक्ष या अप्रत्यक्ष रूप से अपना पक्ष समर्थन करना/कराना एक प्रकार की अनर्हता होगी।
 18. बोलीदाता द्वारा बोली प्रपत्र एवं शर्तों के प्रत्येक पृष्ठ पर शर्तों की स्वीकृति एवं सहमति स्वरूप हस्ताक्षर करने आवश्यक हैं अन्यथा बोली पर विचार नहीं किया जाएगा।
 19. ऑनलाईन बोली अपलोड करते समय निविदा में वांछित दस्तावेज अधिकृत हस्ताक्षरकर्ता द्वारा डिजीटल हस्ताक्षर कर पीडीएफ प्रारूप में स्वीकार किये जायेंगे। किसी भी दस्तावेज पर स्कैन किये गये हस्ताक्षर मान्य नहीं है। सभी दस्तावेज नीली स्याही से हस्ताक्षरित किये जाने चाहिए।
 20. तकनीकी बोली लिफाफे में "Eligibility Criteria/Technical Cover Check List" अनुसार अपेक्षित समस्त दस्तावेज (हस्ताक्षरित गय मुहर) में प्रस्तुत करने होंगे एवं वित्तीय दर प्रस्ताव निर्धारित प्रारूप में पृथक से वित्तीय बोली Online BOQ Xls. में प्रस्तुत करने होंगे। तकनीकी बोली में सफल बोलीदाताओं की ही वित्तीय बोली खोली जाएगी। तकनीकी एवं वित्तीय बोली पृथक-पृथक प्रस्तुत की जानी होगी। अतः बोलीदाता से अपेक्षा है कि बोली सूचना एवं अपेक्षित दस्तावेजों का गलीभांति अध्ययन कर ले।
 21. दरें वित्तीय बोली प्रपत्र Online BOQ Xls. में ही निर्दिष्ट कॉलमों में प्रस्तुत की जावेगी। प्राप्त तकनीकी बोलियों के परीक्षण उपरान्त तकनीकी रूप से सफल बोलीदाता की ही वित्तीय बोली खोली जाएगी। वित्तीय बोली अन्तर्गत जिस बोलीदाता की दरें सभी आईटम्स के लिए प्रस्तुत दरों के कुल योग अनुसार समस्त करें एवं जीएसटी सहित न्यूनतम होगी, वही बोलीदाता सफल बोलीदाता माना जावेगा अर्थात् न्यूनतम बोलीदाता का निर्धारण सभी आईटम्स हेतु प्रस्तुत दरों के कुल योग की न्यूनतम दर के अनुसार किया जावेगा।
 22. वित्तीय बोली में न्यूनतम बोलीदाता के सैंपल का परीक्षण किया जावेगा। सैंपल असफल पाये जाने की स्थिति में एल 2 को एल-1 की दरों पर कार्यादेश दिया जा सकेगा।
 23. वित्तीय बोली में प्रस्तुत दरें गन्तव्य स्थान तक एफ.ओ.आर. कार्यालय प्राचार्य अभियांत्रिकी महाविद्यालय, धौलपुर पर करनी होगी अर्थात् विभाग द्वारा परिवहन संबंधी कोई राशि की पृथक से देयता नहीं होगी।
 24. **सैंपल/नमूनें-**
 1. बोलीदाता को तकनीकी बोली के साथ निविदा में वर्णित सामग्री के स्पेशिफिकेशन के अनुसार ही सैंपल/कैटलॉग उपलब्ध करवाया जाना अनिवार्य है, जिनकी जांच तकनीकी समिति द्वारा की जायेगी। बिना कैटलॉग/नमूनें के प्रस्तुत तकनीकी बोली पर विचार नहीं किया जायेगा। प्रत्येक सैंपल पर ना हटाये जा सकने वाली स्लिप पर बोलीदाता का नाम व आईटम का नाम मय क्रम संख्या लिखा जायेगा। सैंपल/नमूनें पर किसी भी स्थिति में मूल्य अंकित नहीं किया जायेगा। मूल्य अंकित करने की स्थिति में सैंपल को रिजेक्ट/निरस्त समझा जावेगा।
 2. बोलीदाता को प्रत्येक आईटम/उपकरण/उत्पाद की दरें सम्पूर्ण विशिष्टियों सहित देनी होगी अर्थात् उत्पाद/उपकरण का नाम/ट्रेडमार्क/व्यापारिक नाम तथा उपनाम यदि कोई हो आदि सहित दरें प्रस्तुत करेगा तथा प्रत्येक का नमूना कार्यालय, प्राचार्य, अभियांत्रिकी महाविद्यालय, धौलपुर में प्रस्तुत करना होगा।
 3. अनुमोदित सैंपल/नमूनों को संविदा के समाप्त होने के बाद छः माह तक की अवधि तक निःशुल्क रखा जायेगा। इस अवधि में इन नमूनों को प्रतिधारित करने के दौरान उनमें परीक्षण, जांच आदि के दौरान किसी भी नुकसान/टूट-फूट हॉनि के लिए विभाग उत्तरदायी नहीं होगा। नमूनों को वापस लौटाने की व्यवस्था स्वयं बोलीदाता द्वारा की जायेगी। असफल बोलीदाताओं द्वारा प्रस्तुत नमूनों को एवं अनुमोदित फर्म द्वारा प्रदाय किये गये नमूनें को विभाग द्वारा लौटाने हेतु सूचना देने के 2 माह के भीतर यदि प्रदायकर्ता द्वारा नमूनें वापस नहीं लिये जाते हैं तो उन्हें समपह्त कर लिया जायेगा।
 4. प्रदाय की गई सभी वस्तुएं/आईटम्स/उपकरण निविदा में निर्धारित संबंधित सामग्री की विषिष्टा, ट्रेडमार्क के पूर्णतया अनुरूप होगी तथा जहां पर वस्तुओं की आई.एस.आई/बी.आई.एस. विनिर्देश

Kishan
mital

Bhagat
Brajesh

Kishan
mital

के अनुसार अपेक्षा की गयी हो, वहां उन मदों को पूर्णरूप से उन विनिर्देशों के अनुरूप होना चाहिए।

25. निरीक्षण एवं परीक्षण :-

1. तकनीकी बोली के दौरान प्राप्त सामग्री के नमूनों का एवं सफल बोलीदाता द्वारा आपूर्ति की गयी सामग्री/प्रदाय का क्रय समिति/तकनीकी समिति एवं विषय विशेषज्ञों द्वारा निरीक्षण एवं परीक्षण किया जायेगा और यह सुनिश्चित किया जायेगा कि वे निविदा में वर्णित स्पेसिफिकेशन, विनिर्देशों एवं अनुमोदित नमूनों के अनुरूप हैं अथवा नहीं। जहां आवश्यक होगा, वहां प्राप्त प्रदाय/नमूनों का सरकारी प्रयोगशालाओं/प्रतिष्ठित परीक्षण केन्द्रों द्वारा परीक्षण एवं निरीक्षण करवाया जायेगा।
2. आपूर्ति की जाने वाली सामग्री/प्रदाय अनुमोदित नमूनों के अनुरूप नहीं होने पर सम्पूर्ण प्रदाय अथवा उसके अंश को रद्द कर दिया जायेगा। रद्द किये गये प्रदाय/सामग्री को आपूर्तिकर्ता द्वारा 15 दिवस की अवधि में प्राप्त कर सकेगा। इस दौरान विभाग किसी प्रकार की हॉनि, कमी नुकसान के लिए उत्तरदायी नहीं होगा। रद्द किये गये प्रदाय/सामग्री को प्रदायकर्ता द्वारा पुनः अनुमोदित/स्पेसिफिकेशन के अनुरूप उपलब्ध/आपूर्ति करवाये जाने के संबंध में निर्णय लेने हेतु उपापन संस्था सर्वाधिकार सुरक्षित रखती है।
3. परीक्षण प्रभार/पुल्क विभाग द्वारा वहन किया जायेगा। बोलीदाता की अभिशप्ता पर प्रदाय की गयी सामग्री का परीक्षण प्रभार स्वयं बोलीदाता द्वारा वहन किया जायेगा।
4. उपापन संस्था यदि किसी कारणों से निविदा में वर्णित सामग्री से किसी सामग्री/आईटम की खरीद नहीं करती है अथवा कम मात्रा में खरीद करती है तो बोलीदाता किसी क्षतिपूर्ति का दावा करने का हकदार नहीं होगा।
5. अनुमोदित प्रदायकर्ता के लिए यह समझा जाएगा कि उसने प्रदाय किये जाने वाले माल की शर्तों, विनिर्देशों, आकार, मेक/मॉडल, रेखाचित्रों आदि की सावधानीपूर्वक जांच कर ली है। यदि उसे इन शर्तों, विनिर्देशों, आकार, मेक/मॉडल, रेखाचित्रों आदि के सम्पूर्ण/किसी भाग के आषय के बारे में सन्देह हो तो वह संविदा पर हस्ताक्षर करने से पूर्व उपापन संस्था से स्पष्टीकरण प्राप्त कर सकता है।
6. सफल बोलीदाता को क्रय आदेश जारी होने की तिथि से 30 दिवस के भीतर सामग्री की आपूर्ति, स्थापना एवं कमीषनिंग करनी होगी। आपूर्ति की जाने वाली सामग्री उचित पैकिंग में हो ताकि परिवहन के दौरान नुकसान नहीं हो। परिवहन के दौरान प्रदाय की जाने वाली सामग्री में किसी प्रकार की टूट-फूट, नुकसान, हॉनि, या रिसाव या किसी प्रकार की कमी होने के मामलों में अथवा परीक्षण/निरीक्षण के दौरान ऐसी किसी प्रकार हॉनि या कमी पाये जाने पर उसकी पूर्ति के लिए स्वयं बोलीदाता उत्तरदायी होगा।

26. करार का निष्पादन:-

1. कोई उपापन संविदा, ऐसी तारीख से प्रवृत्त होगी, जिसको स्वीकृति पत्र या आशय पत्र बोली लगाने वाले को प्रेषित किया जाता है।
2. सफल बोली लगाने वाले को 7 दिवस के भीतर, जिस पर सफल बोली लगाने वाले को स्वीकृति पत्र या आशय पत्र प्रेषित किया जाता है, उपापन संविदा पर हस्ताक्षर करने होंगे।
3. यदि बोली लगाने वाला, जिसकी बोली स्वीकृत की जा चुकी है, विनिर्दिष्ट कालावधि में लिखित उपापन संविदा पर हस्ताक्षर करने में विफल रहता है या अपेक्षित कार्य सम्पादन प्रतिभूति देने में विफल रहता है तो उपापन संस्था, सफल बोली लगाने वाले के विरुद्ध अधिनियम या इन नियमों के उपबंधों के अनुसार कार्रवाई करेगी। उपापन संस्था, ऐसे मामलों में उपापन प्रक्रिया रद्द कर सकेगी या यदि वह उचित समझे तो, बोली दस्तावेज में उपवर्णित कसौटी और प्रक्रियाओं के अनुसार, न्यूनतम या सर्वाधिक लाभप्रद दरों पर अगले न्यूनतम या सर्वाधिक लाभप्रद दर की बोली लगाने वाले को, स्वीकृति का प्रस्ताव दे सकेगी।
4. बोली लगाने वाले को, उसके खर्च पर, विनिर्दिष्ट मूल्य 500/- रु. के नोन' ज्युडिशियल स्टाम्प पर राजस्थान लोक उपापन में पारदर्शिता अधिनियम, 2012 तथा नियम 2013 के प्रावधान अनुसार करार निष्पादित करना होगा तथा विभाग को मूल करार पत्र उपलब्ध कराना होगा।

Bigs +

to

Millesh ch...

[Signature]

[Signature]

[Signature]

4. बोली लगाने वाले को, उराके खर्च पर, विनिर्दिष्ट मूल्य 500/- रु. के नोन ज्युडिशियल स्टाम्प पर राजस्थान लोक उपापन में पारदर्शिता अधिनियम, 2012 तथा नियम 2013 के प्रावधान अनुसार करार निष्पादित करना होगा तथा विभाग को मूल करार पत्र उपलब्ध कराना होगा।

27. कार्य सम्पादन प्रतिभूति:-

1. सफल बोलीदाता को जिन सामानों (स्टोर्स)/उपकरणों/कार्य/सेवा आपूर्ति के लिये बोलियां स्वीकार की गई हैं उनके बोली मूल्य की 5 प्रतिशत राशि अनुबंध निष्पादन के समय कार्य सम्पादन प्रतिभूति के रूप में जमा करानी होगी।
2. कार्य सम्पादन प्रतिभूति पर विभाग द्वारा ब्याज का भुगतान नहीं किया जायेगा।
3. कार्य सम्पादन प्रतिभूति हेतु बैंक ड्राफ्ट/बैंकर्स चेक प्राचार्य, अभियांत्रिकी महाविद्यालय, धौलपुर के नाम स्वीकार किये जाएंगे।
4. कार्यादेश अनुसार संतोषप्रद रूप से कार्य करने पर एवं इससे संतुष्ट हो जाने पर कि बोलीदाता के विरुद्ध कोई राशि बकाया नहीं है, प्रतिभूति राशि का प्रतिदाय किया जाएगा।
5. कार्य सम्पादन प्रतिभूति की अर्थथना राज्य सरकारके विभागों और ऐसे उपक्रमों, निगमों, स्वायत्त निकायों, रजिस्ट्रीकृत सोसाइटियों, सहकारीसोसाइटियों जो राज्य सरकार के स्वामित्व या नियंत्रण या प्रबंध में हों और केन्द्रीयसरकार के उपक्रमों के सिवाय समस्त सफल बोली लगाने वालों से की जायेगी। तथापि उनसे एक कार्य सम्पादन प्रतिभूति घोषणा ली जायेगी। राज्य सरकार किसी विशिष्ट उपापन या उपापन के किसी प्रवर्ग के मामले में कार्य सम्पादन प्रतिभूति के उपबंध को शिथिल कर सकेगी।

28. कार्य सम्पादन प्रतिभूति निक्षेप का समपहरण:-प्रतिभूति की राशि को पूर्ण या आंशिक रूप से निम्नलिखित मामलों में समपहृत किया जा सकेगा :-

1. जब संविदा के किन्हीं निबंधनों और शर्तों का उल्लंघन किया गया हो।
2. जब बोलीदाता कार्य सन्तोषजनक ढंग से करने में असफल रहा हो।
3. प्रतिभूति निक्षेप को समपहृत करने के मामले में युक्तियुक्त समय पूर्व नोटिस दिया जाएगा। इस संबंध में उपापन संस्था का निर्णय अन्तिम होगा।

29. भुगतान :-

1. भुगतान बोलीदाता द्वारा उचित प्रारूप में सामान्य वित्तीय एवं लेखा नियमों के अनुसार बिल प्रस्तुत करने पर किया जाएगा तथा सभी प्रेषण प्रभार बोलीदाता द्वारा वहन किये जाएंगे।
2. विवादास्पद मदों के संबंध में, नियमानुसार राशि को रोका जाएगा तथा उस विवाद का निपटारा हो जाने पर उसका भुगतान कर दिया जाएगा।
3. उन मामलों के संबंध में जिनमें परीक्षण करने की जरूरत है भुगतान तभी किया जाएगा जब वे परीक्षण कर लिए जाएंगे तथा प्राप्त परीक्षण परिणाम विहित विनिर्देशों के अनुरूप होंगे।
4. फर्म के बिलों से भुगतान के समय नियमानुसार करों की कटौती की जाएगी।

30. परिसमापित नुकसानी :- परिसमापित नुकसानी के साथ सेवा आपूर्ति अवधि में वृद्धि करने के मामले में, वसूली निम्नलिखित प्रतिशतता के आधार पर उन कार्यों के मूल्यों के लिए की जाएगी जिनका बोलीदाता कार्य करने में असफल रहा है (इस संबंध में यदि कोई हो तो बोली प्रपत्र में अंकित की गई शर्तें लागू होंगी)

1. विहित अवधि की एक चौथाई अवधि तक के लिए विलम्ब के लिए 2.5 प्रतिशत
2. एक चौथाई अवधि से अधिक किन्तु विहित अवधि की आधी अवधि से अनधिक के लिए 5 प्रतिशत
3. आधी अवधि से अधिक किन्तु विहित अवधि के तीन चौथाई से अनधिक अवधि के लिए 7.5 प्रतिशत
4. विहित अवधि की तीन चौथाई से अधिक के विलम्ब के लिए 10 प्रतिशत
5. कार्य में विलम्ब की अवधि की गणना करते समय आधे दिन से कम भाग को छोड़ दिया जाएगा।
6. परिसमापितनुकसानी कटौतिराशि अधिकतम 10 प्रतिशत होगी।
7. यदि बोलीदाता, किन्हीं बाधाओं के कारण संविदान्तर्गत कार्य को पूरा करने के लिए समय में वृद्धि कराना चाहता है, तो वह लिखित में उस प्राधिकारी को आवेदन करेगा, जिसने कार्य हेतु आदेश

Mishra
Ansari
Brijesh
Kumar

दिया है किन्तु वह उसके लिए निवेदन बाधा से घटित होने होने पर तुरन्त उसी समय करेगा न कि कार्य पूर्ण होने की निर्धारित तारीख के बाद करेगा।

8. यदि कार्य करने में उत्पन्न हुई बाधा बोलीदाताओ के नियंत्रण से परे कारणों से हुई तो कार्य की अवधि में वृद्धि नियमानुसार परिसमापित नुकसानी कटौति सहित या रहित की जा सकेगी।
9. परिसमापित राशि की कटौती फर्म के लम्बित भुगतान राशि के पेटे जमा राशि में से की जावेगी।
31. **गारंटी :-** बोलीदाता यह गारन्टी देगा कि आपूर्ति की गयी सामग्री/उपकरण सुपुर्दगी एवं स्थापित करने की दिनांक से 3 वर्ष अवधि तक यथा निविदा में विनिर्दिष्ट विवरणानुसार व गुणवत्ता के अनुरूप बनी रहेगी। सुपुर्दगी पश्चात् निर्दिष्ट गारंटी अवधि में यदि आपूर्ति सामग्री गुणवत्ता के अनुरूप नहीं पायी गयी तो उपापन संस्था ऐसी सम्पूर्ण/आंशिक सामग्री या उपकरण को रद्द करने का हकदार होगा। ऐसी रद्द की गयी सामग्री प्रदायकर्ता की जोखिम पर होगी तथा रद्द की गयी सामग्री/उपकरण को प्रदायकर्ता द्वारा बदला जायेगा अन्यथा प्रदायकर्ता से ऐसी हॉनि/कमी के परिणामस्वरूप हुए नुकसान की वसूली उसे देय राशि अथवा विभाग में जमा प्रतिभूति निक्षेप में से की जायेगी। यदि वसूली किया जाना सम्भव नहीं हो तो राजस्थान पीडीआर एक्ट या प्रवृत्त अन्य कानून के अन्तर्गत कार्रवाई की जाएगी। कोई भी सामग्री में विनिर्माण से संबंधित डिफेक्ट नहीं होना चाहिए अन्यथा सामग्री स्वीकार नहीं की जायेगी।
32. यदि कार्य की तात्कालिक आवश्यकता के कारण प्रदाय सामग्री/उपकरण को पूर्ण या आंशिक रूप में बदलना साध्य नहीं समझा जाए तो उपापन संस्था द्वारा बोलीदाता को सुनवाई किये जाने का एक उचित अवसर देकर, ऐसे कारणों से जो अभिलिखित किये जायें, अनुमोदित दरों में से उपयुक्त राशि की कटौती की जायेगी जो कि अन्तिम होगी।
33. **वसूलियाँ :-**परिसमापित नुकसानी, कम प्रदाय, टूट-फूट, रद्द की गयी सामग्री अथवा निविदा में वर्णित किसी अन्य शर्त के तहत हुए नुकसान की वसूली साधारण तौर पर बिल में से कटौती करके की जाएगी। उपापन संस्था राशि को तब तक रोके रखेगी जब तक कि कार्य संतोषजनक रूप से नहीं कर दिया जाता है। यदि बोलीदाता ऐसा नहीं करता है तो राशि की वसूली उसको देय बकायों में से कर ली जाएगी। यदि कोई कार्य शेष रहे तो उसकी मांग बोलीदाता से की जाएगी तथा जब वसूली संभव न हो, तो उपापन संस्था प्रवृत्त विधि का सहारा लेगी।
34. उपापन संस्था न्यूनतम दर को स्वीकार करने के लिए बाध्य नहीं है। उपापन संस्था किसी भी बोली को स्वीकार करने/स्वीकार न करने/निरस्त करने या उसके किसी भी भाग को बिना कोई कारण बताए रद्द करने का सम्पूर्ण अधिकार अपने पास सुरक्षित रखती है। उपापन संस्था का निर्णय वैधानिक तौर से सर्वोत्तम निर्णय माना जाएगा तथा सभी पक्षकारों के लिए मानने के लिए बाध्यकारी रहेगा।
35. यदि बोलीदाता इस बात से ब्यथित है कि उपापन संस्था का कोई निर्णय, कार्यवाही या लोप इस अधिनियम या इसके अधीन जारी नियमों या मार्गदर्शनों के उपबंधों के उल्लंघन में है तो वह राजस्थान लोक उपापन में पारदर्शिता अधिनियम 2012 की धारा 40 के अध्याधीन रहते हुए उपापन संस्था द्वारा जारी आदेश के विरुद्ध प्रथम अपील निर्धारित प्रक्रिया व फीस का भुगतान करने के पश्चात कर सकेगा।
36. समस्त विधिक कार्यवाहियां यदि संस्थित किया जाना आवश्यक हो, किसी भी पक्ष (सरकार या ठेकेदार) द्वारा धोलपुर न्यायिक क्षेत्र पर अधिकारिता रखने वाले न्यायालयों में ही की जाएगी, अन्यत्र नहीं की जाएगी।
37. कार्यादेश जारी करने के उपरान्त प्राप्त सामग्री की जांच क्रय/तकनीकी समिति द्वारा की जाएगी एवं अपेक्षित विनिर्देशों अनुसार सामग्री प्राप्त होने की समिति द्वारा रिपोर्ट प्राप्त होने के उपरान्त ही बोलीदाता को भुगतान किया जाएगा। बोलीदाता द्वारा कार्यादेश जारी होने के उपरान्त विभाग में आपूर्ति की गयी सामग्री की जांच समिति से कराए जाने हेतु प्रतिनिधि को सामग्री सहित भिजवाया जाना अनिवार्य होगा।
38. उपरोक्त शर्तों के अतिरिक्त जहां आवश्यक हो, सामान्य वित्तीय एवं लेखा नियमों, सामान्य वित्तीय एवं लेखा नियमों के फार्म एसआर-14, 15, 16 एवं 17, राजस्थान लोक उपापन में पारदर्शिता अधिनियम

प्रमाण स्वरूप हस्ताक्षर कर दिए हैं) में दी गई समस्त शर्तों से बाध्य होना स्वीकार करते हैं साथ ही इस बात पर भी सहमति देते हैं कि मेरे/हमारे द्वारा बोली के साथ संलग्न किए गए समस्त दस्तावेजों की प्रमाणिकता की जांच मेरे/हमारे द्वारा अपने स्तर पर कर ली गई है। सभी दस्तावेज विधिक/प्रक्रियात्मक/मौलिक रूप से सही है। यदि बोली प्रक्रिया या बोली प्रक्रिया के पश्चात किसी भी स्तर पर उक्त दस्तावेजों की प्रमाणिकता असिद्ध होती है तो इसके लिए मैं/हम पूर्ण रूपेण उत्तरदायी रहूंगा/रहेंगे एवं इसके लिए विभाग किसी भी स्तर पर किसी भी समय बिना नोटिस दिए हमारी बोली/अनुबंध को निरस्त करने/हमारे विरुद्ध कानून/विधिसम्मत दण्डात्मक कार्यवाही करने के लिए सक्षम होगा।

हस्ताक्षर बोलीदाता मय मुहर

Agsts,

35

Mr

Vishnu

Mishra

Brijesh

Mr
to

Annexure- A: Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall-

- a) Not offer any bribe, reward of gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- b) Not misrepresent or omit misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- c) Not indulge in any collusion, Bid rigging or anti competitive behavior to impair the transparency, fairness and progress of the procurement process;
- d) Not misuse any information shared between the procuring entity and the bidders with an intent to gain unfair advantage in the procurement process;
- e) Not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any part or to its property to influence the procurement process;
- f) Not obstruct any investigation or audit of procurement process,
- g) Disclose conflict of interest, if any, and
- h) Disclose any previous transgression with any entity in India or any other country during the last three years or any debarment by any other procuring entity.

CONFLICT OF INTEREST:

The bidder participating in a bidding process must not have a conflict of interest. A conflict of interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.


- 1. A Bidder may be considered to be in conflict of interest with one or more parties in bidding process if, including but not limited to:
 - a. Have controlling partners/shareholders in common; or
 - b. Receive or have received any direct or indirect subsidy from any of them; or
 - c. Have the same legal representative for purposes of the Bid; or
 - d. Have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the Bid of another bidder, or influence the decision of the procuring entity regarding the bidding process; or
 - e. The bidder participates in more than one Bid in a bidding process. Participation by a bidder in more than one Bid will result in the disqualification of all Bids in which the bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a bidder, in more than one Bid; or
 - f. The bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the goods, works or services that are the subject of the Bid; or
 - g. The bidder or any of its affiliates has been hired (or is proposed to be hired by the Procuring Entity as engineer-in charge/consultant for the contract.


Date:


Signature of Bidder with Seal
Name:


Designation:

Address:


CO







Annexure- B: Declaration by the Bidder regarding Qualifications

DECLARATION BY THE BIDDER

In relation to my/our Bid submitted tofor procurement ofM/s..... In response to their notice inviting Bids No.....DatedI/we hereby declare under Section 7 of Rajasthan Transparency in Public Procurement Act, 2012, that:

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the bidding Document issued by the procuring entity;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the Union and the State Government or any local authority as specified in the bidding document;
3. I/we are not insolvent, in receivership bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have been convicted of any criminal offence related to my/our professional conduct or the making of false statements of misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the bidding document, which materially affects fair competition.

Signature of Bidder with Seal

Date:

Name:

Place:

Designation:

Address:

Mishra
Prakash

AW

Bajaj

Bajaj

Written to Bhp

Annexure- C: Grievance Redressal during Procurement process

The designation and address of the First Appellate is

The designation and address of the Second Appellate Authority is

1. Filing an appeal:-

If any bidder or prospective bidder is aggrieved that any decision, action or omission of the procuring entity is in contravention to the provisions of the Act or the Rules or the Guidelines issued there under, he may file an appeal to First Appellate Authority, as specified in the bidding document within a period of ten days, from the date of such decision or action, omission, as the case may be, clearly giving the specific ground or ground on which he feels aggrieved:

Provided that after the declaration of a bidder as successful the appeal may be filed only by a bidder who has participated in procurement proceedings:

Provided further that in case a procuring entity evaluates the technical bids before the opening of the financial Bids, and appeal related to the matter of financial Bids may be filed only by a bidder whose technical Bid is found to be acceptable.

2. The officer to whom an appeal is filed under Para (1) will deal with the appeal as expeditiously as possible and will Endeavour to dispose it off within thirty days from the date of the appeal.

3. If the officer designated under Para (1) fails to dispose of the appeal filed within the period specified in Para (2), or if the bidder or prospective bidder or the procuring entity is aggrieved by the order passed by the First Appellate Authority, the bidder or prospective bidder or the procuring entity, as the case may be may file a second appeal to second Appellate Authority specified in the bidding document in this behalf within fifteen days from the expiry of the period specified in Para (2) or of the date of receipt of the order passed by the First Appellate Authority, as the case may be.

4. Appeal not to lie in certain cases:-

No appeal will lie against any decision of the procuring entity relating to the following matters, namely:-

- (a) Determination of need of procurement;
- (b) Provision limiting participating of bidders in the Bid process;
- (c) The decision of whether or not to enter into negotiations;
- (d) Cancellation of procurement process;
- (e) Applicability of the provisions of confidentiality

5. Form of Appeal:-

Blgn

*Walter
TO RUP*

Brajesh

Tu

Mitesh Chandra

Vinod Kumar

- (a) An appeal under Para (1) or (3) above will be in the annexed Form along with many copies as there are respondents in the appeal.
- (b) Every appeal will be accompanied by an order appealed against, if any affidavit verifying the facts stated in the appeal and proof of payment of fee.
- (c) Every appeal may be presented to First Appellate Authority or Second Appellate Authority, as the case maybe, in person or through registered post or authorized representative.

6. Fee for filling appeal

- (a) Fee for first appeal will be rupees two thousand five hundred and for second appeal will be rupees ten thousand, which will non-refundable.
- (b) The fee will be paid in the form of bank demand draft or banker's cheque of Scheduled Bank in India payable in the name of Appellate Authority concerned.

7. Procedure for disposal of appeal:-

- (a) The First Appellate Authority or Second Appellate Authority, as the case maybe, upon filing of appeal, will issue notice accompanied by copy of appeal, affidavit and documents, if any, to the respondents and fix date of hearing.
- (b) On the date fixed for hearing, the First Appellate Authority or Second Appellate Authority, as the case may be, will,-
 - (i) Hear all the parties to appeal present before him; and
 - (ii) Peruse or inspect documents, relevant records or copies thereof relating to the matter.
- (c) After hearing the parties, perusal or inspection of documents and relevant records or copies thereof relating to the matter, the Appellate Authority concerned will pass an order in writing and provide the copy of order to the parties free of cost.
- (d) The order passed under sub-clause © above will be place on the State Public Procurement Portal.

Date:

Place

Signature of Bidder with Seal

Name:

Designation:

Address:

Handwritten signature

Balraj
Brijesh
Milshchub

Handwritten signature
to sign

Annexure- D: Additional Conditions of Contract

1. Correction of Arithmetic Errors:-

Provided that a financial Bid is substantially responsive, the procuring entity will correct arithmetical errors during evaluation of financial Bids on the following basis:

- (i) If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price will prevail and the total price will be corrected, unless in the opinion of the procuring entity there is an obvious misplacement of the decimal point in the unit price, in which case the total price as quoted will govern and the unit price will be corrected;
- (ii) If there is an error in a total corresponding to the addition or subtraction of subtotals, the sub totals will prevail and the total will be corrected; and
- (iii) If there is a discrepancy between words and figures, the amount in words will prevail, unless the amount expressed in words is related to an arithmetic error, in which case the amount in figures will prevail subject to clause (i) and (ii) above.

If the bidder that submitted the lowest evaluated Bid does not accept the correction of errors, its Bid will be disqualified and its Bid security will be forfeited or its Bid securing declaration will be executed.

2. Procuring Entity's Right to Vary Quantities

The quantity mentioned in the Bid is the minimum approximate quantity that the bidder will have to compulsorily supply to specified destination.

- (a) At the time of award of contract, the quantity of Goods, works or service originally specified in the Bidding Document may be increased or decreased by a specified percentage, but such increase or decrease shall not exceed twenty percent. of the quantity specified in the Bidding Document. It shall be without any change in the unit process or other terms and conditions of the Bid and the conditions of contract.
- (b) If the procuring Entity does not procure any subject matter of procurement or procure less than the quantity specified in the Bidding Document due to change in circumstances, the Bidder shall not be entitled for any claim or compensation except otherwise provided in the conditions of contract.
- (c) In case of procurement of Goods or services, additional quantity may be procured by placing a repeat order on the rates and conditions of the original order. However, the additional quantity will not be more than 50% of the value of Goods of the original contract and shall be within one month from the date of expiry of last supply. If the supplier fails to do so, the Procuring Entity will be free to arrange for the balance supply by limited bidding or otherwise and the extra cost incurred will be recovered from the supplier.

Date:
Place:

Signature of Bidder with Seal

Name:
Designation:
Address:

Bdgm

Mishra
to

Brajesh

Mishra

Higham

Annexure- E: Annual Turnover Statement

The annual turnover of M/s. _____
_____for the past three years are given below and
certified that the statement is true and correct.

Sr. No.	Financial Year	Turnover in Rs.
1.	2023-24	_____
2.	2024-25	_____
3.	2025-26	_____
Total -		Rs. _____

Three Year Annual Average turnovers per annum - Rs. _____

Date:

Place:

Signature of Auditor/Seal

Chartered Accountant

(Name & Address)

Membership No. :

Tel. No. :

Mob. No.:

Vishnu
Mishra

Brijesh
Brijesh
Kumar
TO

Annexure- F: Statement of Past Work Experience and Performance

We(name of firm) do hereby undertake that we have supplied specified items as per details given below:-

Financial Year	Order Placed by (Full address of purchaser with telephone & Fax no.	Order No. and Date & Value of Order	Description of Work	Date of completion of delivery		Remarks indicating reasons for late delivery, if any	Has the Specified Service been supplied satisfactory
				As per contract	Actual		
1	2	3	4	5	6	7	8
2022-23							
2023-24							
2024-25							
2025-26							

Note:

1. It shall be notarized and submitted with technical Bid in original.
2. The above information may be verified from relevant documents of bidder.
3. The bidder shall provide & append copies of work order and submit certificates regarding successful completion of above said work

Date:

Signature of Bidder with Seal

Place:

Name & Address

Bhagat

K. D. S.

Brayesh

Te

M. K. S.

M. K. S.

Annexure- G: Declaration regarding acceptance of Terms & Condition of Bid

(On Rs. 100/- non judicial stamp paper duly attested by Notary Public to be submitted in original also)

Bidder Name.....

I/We confirm that I/We are authorized to submit Bid on behalf of the firm participating in the Bid and have perused the entire Tender/Bid document including all its amendments till date.

Having perused the subject Bid with all amendments (wherever applicable). I/We hereby confirm unconditional acceptance and compliance to abide by all its terms & conditions as mentioned in Tender/Bid document including technical particulars, detailed technical specifications of the product, special terms & conditions and general terms & conditions wherever indicated, offer validity, terms of delivery without any deviations whatsoever:

I/We also confirm acceptance of the all general terms & conditions of Bid document.

I/We certify that the prices quoted against the Bid are competitive and without adopting any unfair/unethical means in including cartelization.

I/we certified that tendering firm has not been black listed/banned/Debarred by any Government Department of the State /PSU from business dealings.

I/We also certified that the information given above is factually correct, true and nothing material has been concealed.

Date:
Place:

Signature of Bidder with Seal
Name & Address

[Handwritten signatures and names]
Mishra
Brijesh
Kumar
Mishra
Mishra
Mishra

Annexure- H: Manufacturer's Authorization Form (MAF)

To be filled by the OEM (indicative format)

To

Principal,
Engineering College,
Dholpur (Raj.)

Subject: Issue of the Manufacturer's Authorization Form (MAF) Reference: NIB/ RFP Ref. No.
_____ dated _____

Sir,

We {name and address of the OEM} who are established and reputed original equipment manufacturers (OEMs) having factories at {addresses of manufacturing location} do hereby authorize {M/s _____} who is our {Distributor/ Channel Partner/ Retailer/ Others <please specify>} to bid, negotiate and conclude the contract with you against the aforementioned reference for the following Items manufactured by us: -

{OEM will mention the details of all the proposed product(s) with their make/ model.}

We undertake to provide OEM Warranty & support as mentioned in Bid for the offered Lab equipments as mentioned in technical specification from the date mentioned in work order.

We hereby confirm that the offered Lab equipments is not declared as End-of-Sale on the last date of bid submission.

We hereby confirm that the offered Lab Equipments is not likely to be declared as End-of-Service/ Support within next 5 years from the date of this letter.

Yours faithfully,

For and on behalf of M/s (Name of the manufacturer)

(Authorized Signatory with seal)

Name, Designation & Contact No.:

Address: _____

Balgi ts,
K. M. S.

Brajesh

TE

Mishra

J. Singh

Annexure-I: Bidder's Authorization Certificate

Authorization letter of a person who is signing the tender documents on behalf of Bidder

(To be filled by bidder)

To,

Principal,

Govt. Engineering College,

Dholpur (Raj.)

I/We (Name/Designation) hereby
declare/certify that

(Name/Designation) is hereby authorized to sign relevant documents on behalf of the
company/firm in dealing with Tender.

She/he is also authorized to attend meetings & submit technical & commercial
information/clarifications as may be required by you in the course of processing the Bid. For the
Purpose of validation, his/her verified signatures are as under.

Thanking you.

Name of Bidder:

Verified Signature

Authorized Signatory:

Seal of the Organization:

Date:

Place:

Gurishwar
Millesh Chandra

Balraj
Brajesh

Dr. Arun
CB

Annexure-J:

ब्लेक लिस्ट/अयोग्य न होने तथा अन्य सक्षमताएं पूरी करने का प्रमाण पत्र

(on 50/- Non Judicial stamp paper, Noterized to be submitted in original also)

मैं/हम घोषणा करता हूँ/करते हैं कि :-

1. हमारी फर्म को किसी भी राजकीय विभाग/राजकीय संस्थान/निगम/बोर्ड आदि के द्वारा किसी प्रकार की Civil Engineering Department Lab सामग्री आदि की आपूर्ति संतोषप्रद रूप से पूर्ण नहीं करने के लिए कोई शास्ति आरोपित नहीं की गई है एवं न ही ब्लेक लिस्ट/अयोग्य घोषित किया गया है।
2. यह कि इस बोली हेतु हमारी फर्म आवश्यक वृत्तिक, तकनीकी, वित्तीय और प्रबंधकीय स्रोत तथा उपापन संस्था द्वारा जारी किये गये बोली दस्तावेजों द्वारा अपेक्षित सक्षमता धारित करती हैं।
3. यह कि हमारी फर्म द्वारा केन्द्र सरकार अथवा राज्य सरकार अथवा यथास्थिति किसी स्थानीय प्राधिकारी को संदेय समस्त करो का भुगतान किया जा चुका है और कोई भी कर बकाया नहीं हैं।
4. यह कि हमारी फर्म दिवालिया, रिसीवर के अधीन, शोधन अक्षम नहीं हैं, न ही किसी न्यायालय या किसी न्यायिक अधिकारी द्वारा प्रशासित कार्यकलाप रखती हैं न ही फर्म का कार्यकलाप निलंबित हैं और न पूर्वगामी कारणों में से किसी के लिये भी विधिक कार्यवाहियों के अध्यधीन हैं।
5. यह कि हमारे वृत्तिक आचरण या उपापन प्रक्रिया के प्रारम्भ के पूर्ववर्ती 3 वर्ष की किसी कालावधि के भीतर कोई उपापन संविदा किये जाने के लिये अपनी अहर्ताओं के बारे में मिथ्या कथन करने या दुर्व्यपदेशन संबंधी किसी दांडिक अपराध के संबंध में हमारी फर्म अथवा फर्म के निदेशक और अधिकारी दोष सिद्ध नहीं हुए हैं ना ही विवर्जन कार्यवाहियों के अनुसरण में अन्यथा निरर्हित हुए हैं।

यदि यह घोषणा असत्य पाई जाए तो किसी भी अन्य कार्यवाही, जो की जा सकती है, पर प्रतिकूल प्रभाव डाले बिना, मेरी/हमारी प्रतिभूति को पूर्ण रूप में समपहत किया जा सकेगा तथा बोली को, जिस सीमा तक उसे स्वीकार किया गया है, रद्द किया जा सकेगा।

बोलीवाता के हस्ताक्षर मय मुहर

Annexure-K: Certificate of Conformity/No Deviation

(To be filed by the bidder)

To,

_____ (Raj.)

CERTIFICATE

This is to certify that, the specifications of Items which I! We have mentioned in the Technical bid, and which I! We shall supply if I! We am! are awarded with the work, are in conformity with the minimum technical specifications of the bidding document and that there are no deviations of any kind from the requirement specifications.

Also, I! we have thoroughly read the bidding document and by signing this certificate, we hereby submit our token of unconditional acceptance to all the terms & conditions of the bidding document without any deviations and assumptions.

I! We also certify that the price I! we have quoted is inclusive of all the cost factors involved in the end-to-end implementation and execution of the project, to meet the desired Standards set out in the bidding Document

Name of Bidder:

Verified Signature

Authorized Signatory:

Seal of the Organization:

Date:

Place:

[Handwritten signature]

[Handwritten signature]

Mishra
[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

Annexure-L: UNDERTAKING ON AUTHENTICITY OF EQUIPMENTS

(On Rs. 50/- non judicial stamp paper duly attested by Notary Public to be submitted in original also)

To

.....
.....

Reference: NIB No. : _____ Dated: _____

This has reference to the items being supplied/quoted to you vide bid ref. No-----
dated-----

We hereby undertake that all the components/parts/assembly used in the equipment shall be genuine, original and new components /parts/assembly from respective OEMs of the products and that no refurbished/duplicate/ second hand components/ parts/ assembly are being used or shall be used. In respect of licensed, we undertake that the same shall be supplied along with the authorized license certificate with our name/logo. Also, that it shall be sourced from the authorized source for use in India.

In case, we are found not complying with above at the time of delivery or during installation, for the equipment already billed, we agree to take back the equipment already supplied at our cost and return any amount paid to us by you in this regard and that you will have the right to forfeit our Bid Security/ SD/ PSD for this bid or debar/ black list us or take suitable action against us.

Name of Bidder:

Verified Signature

Authorized Signatory:

Seal of the Organization:

Date:

Place:

Bidgest
Pradeep
Brijesh
Mitahelulu
Pradeep

Annexure-M:

Form of Bid-Securing Declaration

Date :
Bid No. :
Alternative No. :

To :

We, the undersigned, declare that:

We understand that, according to your conditions, bids must be supported by a Bid-Securing Declaration. We accept that we are required to pay the bid security amount specified in the Term and Condition of Bid, in the following cases, namely :-

- (a) when we withdraw or modify our bid after opening of bids;
- (b) when we do not execute the agreement, if any, after placement of supply/work order within the specified period;
- (c) when we fail to commence the supply of the goods or service or execute work as per supply/work order within the time specified;
- (d) when we do not deposit the performance security within specified period after the supply/work order is placed; and
- (e) if we breach any provision of code of integrity prescribed for bidding specified in the Act and Chapter VI of these rules.

In addition to above, the State Government shall debar us from participating in any procurement process undertaken for a period not exceeding three years in case where the entire bid security or any part thereof is required to be forfeited by procuring entity.

We understand this Bid Securing Declaration shall expire if :-

- (i) we are not the successful Bidder;
- (ii) the execution of agreement for procurement and performance security is furnished by us in case we are successful bidder;
- (iii) thirty days after the expiration of our Bid.
- (iv) the cancellation of the procurement process; or
- (v) the withdrawal of bid prior to the deadline for presenting bids, unless the bidding documents stipulate that no such withdrawal is permitted.

Signed :-----

Name :-----


In the capacity of :-----

Duly authorized to sign the bid for and on behalf of :

Dated on day of


Corporate Seal -----

[Note: In case of a Joint Venture, the Bid Securing Declaration must be signed in name of all partners of the Joint Venture that is submitting the bid.]




नोट - राजस्थान स्टाम्प अधिनियम, 1988 की धारा सपठित अनुसूची के अनुच्छेद 4 के अनुसार घोषणा-पत्र पर 50/- रुपये स्टाम्प ड्यूटी देय है तथा इस स्टाम्प ड्यूटी की राशि पर नियमानुसार 30 प्रतिशत सरचार्ज देय है। उक्त घोषणा-पत्र वित्त (जी.एफ.एण्ड ए.आर.) विभाग द्वारा जारी परिपत्र दिनांक 23.12.2020 के अनुसरण में बोलीदाता द्वारा प्रस्तुत किया जावेगा।









(Dr. Rajat Srivastava)







Handwritten marks in the top right corner, possibly initials or a small diagram.

Bolgsis -

Handwritten signature

Handwritten signature

Handwritten signature

Brajesh